

```

*****
*
* CBIOS FOR CP/M VER 2.2 FOR DISK JOCKEY 2D CONTROLLER (ALL
* REVS, AND MODELS A & B). HANDLES DISKETTES WITH SECTOR SIZES
* OF 128 BYTES SINGLE DENSITY, 256, 512, 1024 BYTES DOUBLE
* DENSITY. THERE ARE CONDITIONAL ASSEMBLIES FOR DISKUS HARD
* DISK CONTROLLER.
*
* WRITTEN BY BOBBY DALE GIFFORD.
* 12/8/80
*
* CUSTOMIZED BY JAY O'BRIEN
* 1/16/82
*
* DISK MAP OF SECTORS USED BY COLD BOOT, WARM BOOT, FIRMWARE,
* AND CP/M:
*
* TRK 0 SEC 1 = FIRST SECTOR OF COLD BOOT.          E700H
*           2 = COLD BOOT 256.                        80H
*           3 = COLD BOOT 512.                        80H
*           4 = COLD BOOT 1024.                       80H
*           5 = WARM BOOT 256.                        80H
*           6 = WARM BOOT 512.                        80H
*           7 = WARM BOOT 1024.                       80H
*           8 = COLD/WARM BOOT.                       2C00H
*           9 = FIRMWARE.                             E400H
*           10 = FIRMWARE+80H.                         E480H
*           11 = FIRMWARE+100H                        E500H
*           12 = FIRMWARE+180H.                       E580H
*           13 = FIRMWARE+200H.                       E600H
*           14 = FIRMWARE+280H.                       E680H
*           15 = FIRMWARE+300H.                       E700H
*           16 = FIRMWARE+380H.                       E780H
*           17 = CCP.                                  2700H +A000 = C700
*           18 = CCP+80H.                              2780H
*           19 = CCP+100H.                             2800H
*           20 = CCP+180H.                             2880H
*           21 = CCP+200H.                             2900H
*           22 = CCP+280H.                             2980H
*           23 = CCP+300H.                             2A00H
*           24 = CCP+380H.                             2A80H
*           25 = CCP+400H.                             2B00H
*           26 = CCP+480H.                             2B80H
*           = REST OF CP/M.                            2C00H-4FFFH
*
*****

```

TITLE '*** Cbios For CP/M Ver. 2.2 ***'

```

*****
*
* THE FOLLOWING REVISION NUMBER IS IN REFERENCE TO THE CP/M
* 2.2 CBIOS.
*
*****

```


CBIOS7A.PRN
 3/23/82
 DJ AT FORD
 FLOPPIES=A,B
 HD=C,D,E
 VIOX VIDED
 60K

ED82 - A000 = A082
 - C700

 2682

- 2700

 2682



001C = REVNUM EQU 28 ;CBIOS REVISION NUMBER
 0016 = CPMREV EQU 22 ;CP/M REVISION NUMBER

 *
 * THE FOLLOWING EQUATES SET UP THE RELATIONSHIP BETWEEN THE *
 * 2D FLOPPIES AND THE HARD DISK CONTROLLERS. *
 *

0000 = FIRST EQU 0 ;0 = FLOPPIES ARE A,B,C,D DRIVES AND
 ; HARD DISK ARE E,F,G,H
 ;1 = HARD DISKS ARE A,B,C,D DRIVES AND
 ; FLOPPIES ARE E,F,G,H
 0001 = MAXHD EQU 1 ;SET TO NUMBER OF HARD DISKS
 0002 = MAXFLOP EQU 2 ;SET TO NUMBER OF FLOPPIES
 0001 = M26 EQU 1 ;SET ONLY ONE OF THESE VARIABLES
 0000 = M20 EQU 0
 0000 = M10 EQU 0

IF M10 OR M20
 SDELAY EQU 0 ;SOFTWARE HEAD SETTLE DELAY (0 = NO, 1 = YES)
 ELSE
 0001 = SDELAY EQU 1
 ENDIF

001A = MREV EQU 26*M26+20*M20+10*M10 ;HARD DISK TYPE
 0003 = LOGDSK EQU 3*M26+3*M20+2*M10 ;LOGICAL DISKS PER DRIVE
 0020 = HDSPT EQU 32*M26+21*M20+21*M10 ;SECTORS PER TRACK

 *
 * THE FOLLOWING EQUATES RELATE THE THINKER TOYS 2D CONTROLLER. *
 * IF THE CONTROLLER IS NON STANDARD (0E000H) ONLY THE ORIGIN *
 * EQUATE NEED BE CHANGED. THIS VERSION OF THE CBIOS WILL WORK *
 * WITH 2D CONTROLLER BOARDS REV 0, 1, 3, 3.1, 4, MODEL B. *
 *

IF MAXFLOP NE 0 ;INCLUDE DISCUS 2D ?
 F000 = ORIGIN EQU 0F000H
 F400 = DJRAM EQU ORIGIN+400H ;DISK JOCKEY 2D RAM ADDRESS
 F400 = DJBOOT EQU DJRAM ;DISK JOCKEY 2D INITIALIZATION
 F003 = DJCIN EQU ORIGIN+3H ;DISK JOCKEY 2D CHARACTER INPUT ROUTINE
 F006 = DJCOUT EQU ORIGIN+6H ;DISK JOCKEY 2D CHARACTER OUTPUT ROUTINE
 F409 = DJHOME EQU DJRAM+9H ;DISK JOCKEY 2D TRACK ZERO SEEK
 F40C = DJTRK EQU DJRAM+0CH ;DISK JOCKEY 2D TRACK SEEK ROUTINE
 F40F = DJSEC EQU DJRAM+0FH ;DISK JOCKEY 2D SET SECTOR ROUTINE
 F412 = DJDMA EQU DJRAM+012H ;DISK JOCKEY 2D SET DMA ADDRESS
 F415 = DJREAD EQU DJRAM+15H ;DISK JOCKEY 2D READ ROUTINE
 F418 = DJWRITE EQU DJRAM+18H ;DISK JOCKEY 2D WRITE ROUTINE
 F41B = DJSEL EQU DJRAM+1BH ;DISK JOCKEY 2D SELECT DRIVE ROUTINE
 F021 = DJTSTAT EQU ORIGIN+21H ;DISK JOCKEY 2D TERMINAL STATUS ROUTINE

```
F427 = DJSTAT EQU DJRAM+27H ;DISK JOCKEY 2D STATUS ROUTINE
F42A = DJERR EQU DJRAM+2AH ;DISK JOCKEY 2D ERROR, FLASH LED
F42D = DJDEN EQU DJRAM+2DH ;DISK JOCKEY 2D SET DENSITY ROUTINE
F430 = DJSIDE EQU DJRAM+30H ;DISK JOCKEY 2D SET SIDE ROUTINE
0008 = DBLSID EQU 8 ;SIDE BIT FROM CONTROLLER
      ENDIF
```

```
*****
*
* THE FOLLOWING EQUATES ARE FOR THE DISKUS HARD DISK WANTED.
*
*****
```

```
      IF MAXHD NE 0 ;WANT HARD DISK INCLUDED ?
0050 = HDORG EQU 50H ;HARD DISK CONTROLLER ORIGIN
0050 = HDSTAT EQU HDORG ;HARD DISK STATUS
0050 = HDCNTL EQU HDORG ;HARD DISK CONTROL
0053 = HDDATA EQU HDORG+3 ;HARD DISK DATA
0052 = HDFUNC EQU HDORG+2 ;HARD DISK FUNCTION
0051 = HDCMND EQU HDORG+1 ;HARD DISK COMMAND
0051 = HDRESLT EQU HDORG+1 ;HARD DISK RESULT
0002 = RETRY EQU 2 ;RETRY BIT OF RESULT
0001 = TKZERO EQU 1 ;TRACK ZERO BIT OF STATUS
0002 = OPDONE EQU 2 ;OPERATION DONE BIT OF STATUS
0004 = COMPLT EQU 4 ;COMPLETE BIT OF STATUS
0008 = TMOUT EQU 8 ;TIME OUT BIT OF STATUS
0010 = WFAULT EQU 10H ;WRITE FAULT BIT OF STATUS
0020 = DRVRDY EQU 20H ;DRIVE READY BIT OF STATUS
0040 = INDEX EQU 40H ;INDEX BIT OF STATUS
0004 = PSTEP EQU 4 ;STEP BIT OF FUNCTION
00FB = NSTEP EQU 0FBH ;STEP BIT MASK OF FUNCTION
0004 = HDRLEN EQU 4 ;SECTOR HEADER LENGTH
0200 = SECLN EQU 512 ;SECTOR DATA LENGTH
000F = WENABL EQU 0FH ;WRITE ENABLE
000B = WRESET EQU 0BH ;WRITE RESET OF FUNCTION
0005 = SCENBL EQU 5 ;CONTROLLER CONTROL
0007 = DSKCLK EQU 7 ;DISK CLOCK FOR CONTROL
00F7 = MDIR EQU 0F7H ;DIRECTION MASK FOR FUNCTION
00FC = NULL EQU 0FCH ;NULL COMMAND
0000 = IDBUFF EQU 0 ;INITIALIZE DATA COMMAND
0008 = ISBUFF EQU 8 ;INITIALIZE HEADER COMMAND
0001 = RSECT EQU 1 ;READ SECTOR COMMAND
0005 = WSECT EQU 5 ;WRITE SECTOR COMMAND
      ENDIF
```

```
*****
*
* CP/M SYSTEM EQUATES. IF RECONFIGURATION OF THE CP/M SYSTEM
* IS BEING DONE, THE CHANGES CAN BE MADE TO THE FOLLOWING
* EQUATES.
*
*****
```

```
003C = MSIZE EQU 60 ;MEMORY SIZE OF TARGET CP/M
A000 = BIAS EQU (MSIZE-20)*1024 ;MEMORY OFFSET FROM 20K SYSTEM
C700 = CCP EQU 2700H+BIAS ;CONSOLE COMMAND PROCESSOR
```

```

CF00 = BDOS EQU CCP+800H ;BDOS ADDRESS
DD00 = BIOS EQU CCP+1600H ;CBIOS ADDRESS
4A00 = OFFSETC EQU 2700H-BIOS ;OFFSET FOR SYSGEN
0004 = CDISK EQU 4 ;ADDRESS OF LAST LOGGED DISK
0080 = BUFF EQU 80H ;DEFAULT BUFFER ADDRESS
0100 = TPA EQU 100H ;TRANSIENT MEMORY
00C0 = INTIOBY EQU 192 ;INITIAL IOBYTE
0003 = IOBYTE EQU 3 ;IOBYTE LOCATION
0000 = WBOT EQU 0 ;WARM BOOT JUMP ADDRESS
0005 = ENTRY EQU 5 ;BDOS ENTRY JUMP ADDRESS
    
```

```

*****
*
* THE FOLLOWING ARE INTERNAL CBIOS EQUATES. MOST ARE MISC.
* CONSTANTS.
*
*****
    
```

```

000A = RETRIES EQU 10 ;MAX RETRIES ON DISK I/O BEFORE ERROR
000D = ACR EQU 0DH ;A CARRIAGE RETURN
000A = ALF EQU 0AH ;A LINE FEED
001A = CLEAR EQU 1AH ;CLEAR SCREEN FOR VIO-X
0003 = AETX EQU 3 ;ETX CHARACTER
0006 = AACK EQU 6 ;ACK CHARACTER
    
```

```

*****
*
* THE JUMP TABLE BELOW MUST REMAIN IN THE SAME ORDER, THE
* ROUTINES MAY BE CHANGED, BUT THE FUNCTION EXECUTED MUST BE
* THE SAME.
*
*****
    
```

```

DD00          ORG      BIOS          ;CBIOS STARTING ADDRESS

DD00 C3DAE5    WBOOTE  JMP      CBOOT    ;COLD BOOT ENTRY POINT
DD03 C3BCDE    WBOOTE  JMP      WBOOT    ;WARM BOOT ENTRY POINT
DD06 C336DD    WBOOTE  JMP      CONST    ;CONSOLE STATUS ROUTINE
DD09 C342DD    WBOOTE  JMP      CONIN    ;CONSOLE INPUT
DD0C C357DD    COUT    JMP      CONOUT  ;CONSOLE OUTPUT
DD0F C377DD    COUT    JMP      LIST    ;LIST DEVICE OUTPUT
DD12 C36CDD    COUT    JMP      PUNCH   ;PUNCH DEVICE OUTPUT
DD15 C362DD    COUT    JMP      READER  ;READER DEVICE INPUT
DD18 C351DF    COUT    JMP      HOME    ;HOME DRIVE
DD1B C393DF    COUT    JMP      SETDRV  ;SELECT DISK
DD1E C353DF    COUT    JMP      SETTRK  ;SET TRACK
DD21 C345DF    COUT    JMP      SETSEC  ;SET SECTOR
DD24 C34BDF    COUT    JMP      SETDMA  ;SET DMA ADDRESS
DD27 C399E0    COUT    JMP      READ    ;READ THE DISK
DD2A C392E0    COUT    JMP      WRITE   ;WRITE THE DISK
DD2D C382DD    COUT    JMP      LISTST  ;LIST DEVICE STATUS
DD30 C358DF    COUT    JMP      SECTRAN ;SECTOR TRANSLATION

DD33 C31BF4    DJDRV   IF      MAXFLOP NE 0
                DJDRV   JMP      DJSEL    ;HOOK FOR SINGLE.COM PROGRAM
                ELSE
    
```

```
JMP DONOP
ENDIF
```

```
*****
*
* TERMINAL DRIVER ROUTINES. IOBYTE IS INITIALIZED BY THE COLD
* BOOT ROUTINE, TO MODIFY, CHANGE THE "INTIOBY" EQUATE. THE
* I/O ROUTINES THAT FOLLOW ALL WORK EXACTLY THE SAME WAY. USING
* IOBYTE, THEY OBTAIN THE ADDRESS TO JUMP TO IN ORDER TO EXECUTE
* THE DESIRED FUNCTION. THERE IS A TABLE WITH FOUR ENTRIES FOR
* EACH OF THE POSSIBLE ASSIGNMENTS FOR EACH DEVICE. TO MODIFY
* THE I/O ROUTINES FOR A DIFFERENT I/O CONFIGURATION, JUST
* CHANGE THE ENTRIES IN THE TABLES.
*
```

```
F003 = CITY EQU DJCIN ;INPUT FROM THE DISK JOCKEY 2D
F006 = COTTY EQU DJCOUT ;OUTPUT TO THE DISK JOCKEY 2D
```

```
*****
*
* CONST: GET THE STATUS FOR THE CURRENTLY ASSIGNED CONSOLE
* DEVICE. THE CONSOLE DEVICE CAN BE GOTTEN FROM IOBYTE,
* THEN A JUMP TO THE CORRECT CONSOLE STATUS ROUTINE IS
* PERFORMED.
*
```

```
DD36 21B0DD CONST LXI H,CSTBLE ;BEGINNING OF JUMP TABLE
DD39 C348DD JMP CONIN1 ;SELECT CORRECT JUMP
```

```
*****
*
* CSREADER: IF THE CONSOLE IS ASSIGNED TO THE READER THEN A
* JUMP WILL BE MADE HERE, WHERE ANOTHER JUMP WILL
* OCCUR TO THE CORRECT READER STATUS.
*
```

```
DD3C 21B8DD CSREADR LXI H,CSRTBLE ;BEGINNING OF READER STATUS TABLE
DD3F C365DD JMP READERA
```

```
*****
*
* CONIN: TAKE THE CORRECT JUMP FOR THE CONSOLE INPUT ROUTINE.
* THE JUMP IS BASED ON THE TWO LEAST SIGNIFICANT BITS OF
* IOBYTE.
*
```

```
DD42 CD0CE1 CONIN CALL FLUSH ;FLUSH THE DISK BUFFER
DD45 2188DD LXI H,CITBLE ;BEGINNING OF CHARACTER INPUT TABLE
```

```
*
* ENTRY AT CONIN1 WILL DECODE THE TWO LEAST SIGNIFICANT BITS
* OF IOBYTE. THIS IS USED BY CONIN, CONOUT, AND CONST.
```

*

DD48 3A0300 CONIN1 LDA IOBYTE
DD4B 17 RAL

*

* ENTRY AT SELDEV WILL FORM AN OFFSET INTO THE TABLE POINTED
* TO BY H&L AND THEN PICK UP THE ADDRESS AND JUMP THERE.
*

DD4C E606 SELDEV ANI 6H ;STRIP OFF UNWANTED BITS
DD4E 1600 MVI D,0 ;FORM OFFSET
DD50 5F MOV E,A
DD51 19 DAD D ;ADD OFFSET
DD52 7E MOV A,M ;PICK UP HIGH BYTE
DD53 23 INX H
DD54 66 MOV H,M ;PICK UP LOW BYTE
DD55 6F MOV L,A ;FORM ADDRESS
DD56 E9 PCHL ;GO THERE !

*
* CONOUT: TAKE THE PROPER BRANCH ADDRESS BASED ON THE TWO LEAST *
* SIGNIFICANT BITS OF IOBYTE. *
*

DD57 C5 CONOUT PUSH B ;SAVE THE CHARACTER
DD58 CD0CE1 CALL FLUSH ;FLUSH THE DISK BUFFER
DD5B C1 POP B ;RESTORE THE CHARACTER
DD5C 2190DD LXI H,COTBLE ;BEGINNING OF THE CHARACTER OUT TABLE
DD5F C348DD JMP CONIN1 ;DO THE DECODE

*
* READER: SELECT THE CORRECT READER DEVICE FOR INPUT. THE *
* READER IS SELECTED FROM BITS 2 AND 3 OF IOBYTE. *
*

DD62 21A8DD READER LXI H,RTBLE ;BEGINNING OF READER INPUT TABLE

*
* ENTRY AT READERA WILL DECODE BITS 2 & 3 OF IOBYTE, USED
* BY CSREADER.
*

DD65 3A0300 READERA LDA IOBYTE

*
* ENTRY AT READER1 WILL SHIFT THE BITS INTO POSITION, USED
* BY LIST AND PUNCH.
*

DD68 1F READR1 RAR
DD69 C34CDD JMP SELDEV

*
* PUNCH: SELECT THE CORRECT PUNCH DEVICE. THE SELECTION COMES *
* FROM BITS 4&5 OF IOBYTE. *
*

```
DD6C 21A0DD PUNCH LXI H,PTBLE ;BEGINNING OF PUNCH TABLE
DD6F 3A0300 LDA IOBYTE
```

*
* ENTRY AT PNCH1 ROTATES BITS A LITTLE MORE IN PREP FOR *
* SELDEV, USED BY LIST. *
*

```
DD72 1F PNCH1 RAR
DD73 1F RAR
DD74 C368DD JMP READR1
```

*
* LIST: SELECT A LIST DEVICE BASED ON BITS 6&7 OF IOBYTE *
*

```
DD77 2198DD LIST LXI H,LTBLE ;BEGINNING OF THE LIST DEVICE ROUTINES
DD7A 3A0300 LIST1 LDA IOBYTE
DD7D 1F RAR
DD7E 1F RAR
DD7F C372DD JMP PNCH1
```

*
* LISTST: GET THE STATUS OF THE CURRENTLY ASSIGNED LIST DEVICE *
*

```
DD82 21C0DD LISTST LXI H,LSTBLE ;BEGINNING OF THE LIST DEVICE STATUS
DD85 C37ADD JMP LIST1
```

*
* IF CUSTOMIZING I/O ROUTINES IS BEING PERFORMED, THE TABLE *
* BELOW SHOULD BE MODIFIED TO REFLECT THE CHANGES. ALL I/O *
* DEVICES ARE DECODED OUT OF IOBYTE AND THE JUMP IS TAKEN FROM *
* THE FOLLOWING TABLES. *
*

*
* CONSOLE INPUT TABLE *
*

```
DD88 F3DD CITBLE DW CIUC1 ;INPUT FROM USER CONSOLE 1 (CURRENTLY
; SWBD PARALLEL PORT 4)
```

```

DD8A 08DE      DW      CICRT      ;INPUT FROM CRT (CURRENTLY SWITCHBOARD
;              SERIAL PORT 1)
DD8C 62DD      DW      READER     ;INPUT FROM READER (DEPENDS ON READER
;              SELECTION)
DD8E 03F0      DW      CTTY       ;INPUT FROM TTY (CURRENTLY INPUT FROM
;              DISK JOCKEY 2D)
    
```

*
* CONSOLE OUTPUT TABLE
*

```

DD90 3BDE      COTBLE DW      COCRT     ;OUTPUT TO CRT
;
DD92 3BDE      DW      COCRT     ;OUTPUT TO CRT
;
DD94 77DD      DW      LIST      ;OUTPUT TO LIST DEVICE (DEPENDS ON
;              BITS 6&7 OF IOBYTE)
DD96 06F0      DW      COTTY     ;OUTPUT TO TTY (CURRENTLY OUTPUT TO
;              DISK JOCKEY 2D)
    
```

*
* LIST DEVICE TABLE
*

```

DD98 06F0      LTBLE  DW      COTTY     ;OUTPUT TO TTY (CURRENTLY ASSIGNED
;              BY INTIOBY, OUTPUT TO 2D)
DD9A 46DE      DW      COPTR     ;OUTPUT TO PRINTER OK 1
;
DD9C C9DD      DW      COLPT     ;OUTPUT TO LINE PRINTER (CURRENTLY
;              SWITCHBOARD SERIAL PORT 1)
DD9E D4DD      DW      COUL1     ;OUTPUT TO USER LINE PRINTER 1 (CURRENTLY
;              SWITCHBOARD SERIAL PORT 1) 1P51
    
```

*
* PUNCH DEVICE TABLE
*

```

DDA0 06F0      PTBLE  DW      COTTY     ;OUTPUT TO THE TTY (CURRENTLY ASSIGNED
;              BY INTIOBY, OUTPUT TO 2D)
DDA2 46DE      DW      COPTR     ;OUTPUT TO PRINTER
;
DDA4 C9DD      DW      COUP1     ;OUTPUT TO USER PUNCH 1 (CURRENTLY
;              SWITCHBOARD SERIAL PORT 1)
DDA6 C9DD      DW      COUP2     ;OUTPUT TO USER PUNCH 2 (CURRNTLLY
;              SWITCHBOARD SERIAL PORT 1)
    
```

*
* READER DEVICE INPUT TABLE
*

```

DDA8 03F0      RTBLE  DW      CTTY       ;INPUT FROM TTY (CURRENTLY ASSIGNED
;              BY INTIOBY, INPUT FROM 2D)
DDAA 08DE      DW      CIPTR     ;INPUT FROM PAPER TAPE READER (CURRENTLY
;              SWITCHBOARD SERIAL PORT 1)
DDAC 08DE      DW      CIUR1     ;INPUT FROM USER READER 1 (CURRENTLY
;              SWITCHBOARD SERIAL PORT 1)
DDAE 08DE      DW      CIUR2     ;INPUT FROM USER READER 2 (CURRENTLY
    
```


; SWITCHBOARD SERIAL PORT 1)

*
* CONSOLE STATUS TABLE
*

DDB0 FFDD CSTBLE DW CSUC1 ;STATUS FROM SWBD PARALLEL PORT 4, AS
; READ FROM ATTN BIT 0)
DDB2 1CDE DW CSCRT ;STATUS FROM CRT (CURRENTLY SWITCHBOARD
; SERIAL PORT 1)
DDB4 3CDD DW CSREADR ;STATUS FROM READER (DEPENDS ON READER DEVICE)
; DDB6 14DE DW CSTTY ;STATUS OF TTY (CURRENTLY STSTUS FROM
; DISK JOCKEY 2D)

*
* STATUS FROM READER DEVICE
*

DDB8 14DE CSRTBLE DW CSTTY ;STATUS FROM TTY (CURRENTLY ASSIGNED
; BY INTIOBY, STATUS OF 2D)
DDBA 1CDE DW CSPTR ;STATUS FROM PAPER TAPE READER (CURRENTLY
; SWITCHBOARD SERIAL PORT 1)
DDBC 1CDE DW CSUR1 ;STATUS FROM USER READER 1 (CURRENTLY
; SWITCHBOARD SERIAL PORT 1)
DDBE 1CDE DW CSUR2 ;STATUS OF USER READER 2 (CURRENTLY
; SWITCHBOARD SERIAL PORT 1)

*
* STATUS FROM LIST DEVICE
*

DDC0 2ADE LSTBLE DW READY ;CONSOLE ALWAYS READY
DDC2 2ADE DW READY ;GET LIST STATUS
DDC4 25DE DW LSLPT
DDC6 25DE DW LSLPT

*
* ROUTINES FOR MY SYSTEM. J. J. O'BRIEN
*

DDC8 00

NOP

*
* THE FOLLOWING EQUATES SET OUTPUT DEVICE TO OUTPUT TO THE
* SWITCHBOARD SERIAL PORT 1.
*

DDC9 = COPTP EQU \$;OUTPUT FROM PAPER TAPE PUNCH
DDC9 = COUP1 EQU \$;OUTPUT FROM USER PUNCH 1
DDC9 = COUP2 EQU \$;OUTPUT FROM USER PUNCH 2
DDC9 DB02 COLPT IN 2 ;OUTPUT FROM LINE PRINTER,GET STATUS
DDCB E680 ANI 80H ;WAIT UNTIL OK TO SEND
DDCD CAC9DD JZ COLPT ;
DDD0 79 MOV A,C ;OUTPUT THE CHARACTER

DDD1 D301 OUT 1
 DDD3 C9 RET

 *
 * CUSTOM I/O PRINTER DRIVER FOR DIABLO PRINTER WITH 1200 BAUD *
 * ETX/ACK HANDSHAKE. *
 *

DDD4 CDC9DD COUL1 CALL COLPT ;OUTPUT THE CHARACTER
 DDD7 3AF2DD LDA COUNT
 DDDA 3D DCR A
 DDDB 32F2DD STA COUNT
 DDDE C0 RNZ
 DDDF 3E4E MVI A,78
 DDE1 32F2DD STA COUNT
 DDE4 0E03 MVI C,AETX
 DDE6 CDC9DD CALL COLPT
 DDE9 CD08DE PWAIT CALL CIPTR
 DDEC FE06 CPI AACK
 DDEE C2E9DD JNZ PWAIT
 DDF1 C9 RET

DDF2 32 COUNT DB 50

 *
 * THE FOLLOWING EQUATES SET THE INPUT TO COME FROM THE SWBD *
 * PARALLEL PORT 4, WITH STATUS ON ATTENTION PORT BIT 0. *
 *

DDF3 DB03 CIUC1 IN 3 ;GET ATTENTION BYTE
 DDF5 E601 ANI 1 ;GET BIT 0 ONLY
 DDF7 CAF3DD JZ CIUC1 ;WAIT FOR CHARACTER
 DDFA DB04 IN 4 ;GET CHARACTER
 DDFC E67F ANI 7FH ;STRIP OFF THE PARITY
 DDFE C9 RET

DDFF DB03 CSUC1 IN 3 ;GET ATTENTION BYTE
 DE01 E601 ANI 1 ;GET BIT 0 ONLY
 DE03 EE01 XRI 1 ;CHANGE POLARITY
 DE05 C317DE JMP STAT ;RETURN PROPER INDICATION

 *
 * THE FOLLOWING EQUATES SET THE INPUT FROM THE DEVICES TO COME *
 * FROM THE SWITCHBOARD SERIAL PORT 1. *
 *

DE08 = CICRT EQU \$;INPUT FROM CRT
 DE08 = CIUR1 EQU \$;INPUT FROM USER READER 1
 DE08 = CIUR2 EQU \$;INPUT FROM USER READER 2
 DE08 DB02 CIPTR IN 2 ;INPUT FROM PAPER TAPE READER, GET STATUS

```

DE0A E640      ANI      40H      ;WAIT FOR CHARACTER
DE0C CA08DE    JZ        CIPTR
DE0F DB01      IN        1
DE11 E67F      ANI      7FH      ;STRIP OFF THE PARITY
DE13 C9        RET
    
```

```

*****
*
*  CONSOLE STATUS ROUTINES, TEST IF A CHARACTER HAS ARRIVED.
*
*****
    
```

```

DE14 CD21F0    CSTTY   CALL    DJTSTAT    ;STATUS FROM DISK JOCKEY 2D
DE17 3E00      STAT    MVI     A,0          ;PREP FOR ZERO RETURN
DE19 C0        RNZ
DE1A 3D        DCR     A          ;NOTHING FOUND
DE1B C9        RET          ;RETURN WITH 0FFH
    
```

```

*****
*
*  THE FOLLOWING EQUATES CAUSE THE DEVICES TO GET STATUS FROM
*  THE SWITCHBOARD SERIAL PORT 1.
*
*****
    
```

```

DE1C =         CSUR1   EQU     $          ;STATUS OF USER READER 1
DE1C =         CSUR2   EQU     $          ;STATUS OF USER READER 2
DE1C =         CSPTR   EQU     $          ;STATUS OF PAPER TAPE READER
DE1C DB02      CSCRT   IN      2          ;STATUS FROM CRT, GET STATUS
DE1E E640      ANI     40H          ;STRIP OF DATA READY BIT
DE20 EE40      XRI     40H          ;MAKE CORRECT POLARITY
DE22 C317DE    JMP     STAT          ;RETURN PROPER INDICATION
    
```

```

*****
*
*  LIST DEVICE STATUS ROUTINES.
*
*****
    
```

```

DE25 DB02      LSLPT   IN      2          ;ALL OTHER DEVICES WAIT
DE27 E680      ANI     80H
DE29 C8        RZ
DE2A 3EFF      READY  MVI     A,0FFH
DE2C C9        RET
    
```

```

*****
*
*  THIS INITIALIZING ROUTINE SAMPLES BIT 0 OF SWBD PORT 7 TO
*  DETERMINE IF THE KEYBOARD IS PLUGGED IN. IF THE KEYBOARD IS
*  PLUGGED IN, THE LSB RETURNS A 0. OTHERWISE, IT IS A 1.
*  THIS 1 IS ADDED TO IOBYTE TO CHANGE THE CONSOLE INPUT FROM
*  THE SWBD PARALLEL PORT 4 (THE KEYBOARD) TO THE SWBD SERIAL
*  PORT THAT RECEIVES RS232 DATA FROM THE RS232 TERMINAL.
*
*****
    
```

```

DE2D 0E1A      TINIT  MVI      C,CLEAR      ;INITIALIZE THE TERMINAL ROUTINE
DE2F DB07      IN        7              ;GET KEYBOARD INTERLOCK BYTE
DE31 E601      ANI        1              ;GET BIT 1 ONLY
DE33 C6C0      ADI        INTIOBY     ;ADD INTIOBY TO KEYBOARD BIT
DE35 320300    STA        IOBYTE     ;INITIALIZE IOBYTE
DE38 C30CDD    JMP        COUT

```

```

*****
*
* VIO-X VIDEO DRIVER
*
*****

```

```

DE3B DB09      COCRT  IN        9              ;READ STATUS PORT
DE3D E601      ANI        1              ;MASK TXRDY BIT
DE3F CA3BDE    JZ         COCRT       ;WAIT FOR READY
DE42 79        MOV        A,C          ;GET CHAR
DE43 D308      OUT        8              ;OUTPUT IT
DE45 C9        RET         ;ALL DONE

```

```

*****
*
* ROUTINE FOR OKIDATA PRINTER
* PRINTER IS ON PORT 0 WITH PRINTER READY ON PORT 5 BIT 1
*
*****

```

```

DE46 DB02      COPTR  IN        2              ;INPUT FROM PORT 2
DE48 E608      ANI        8              ;WAIT UNTIL OK TO SEND
DE4A CA46DE    JZ         COPTR
DE4D DB05      COPTR1 IN        5              ;BUFFER FULL?
DE4F E601      ANI        1
DE51 CA4DDE    JZ         COPTR1     ;WAIT UNTIL PRINTER READY
DE54 79        MOV        A,C          ;OUTPUT THE CHARACTER
DE55 D300      OUT        0
DE57 C9        RET

```

```

*****
*
* GOCPM IS THE ENTRY POINT FROM COLD BOOTS, AND WARM BOOTS. IT
* INITIALIZES SOME OF THE LOCATIONS IN PAGE 0, AND SETS UP THE
* INITIAL DMA ADDRESS (80H).
*
*****

```

```

DE58 218000    GOCPM  LXI        H,BUFF      ;SET UP INITIAL DMA ADDRESS
DE5B CD4BDF    CALL       SETDMA
DE5E 3EC3      MVI        A,(JMP)         ;INITIALIZE JUMP TO WARM BOOT
DE60 320000    STA        WBOT
DE63 320500    STA        ENTRY         ;INITIALIZE JUMP TO BDOS
DE66 2103DD    LXI        H,WBOOTE      ;ADDRESS IN WARM BOOT JUMP
DE69 220100    SHLD      WBOT+1
DE6C 2106CF    LXI        H,BDOS+6     ;ADDRESS IN BDOS JUMP
DE6F 220600    SHLD      ENTRY+1
DE72 AF       XRA        A             ;A ← 0
DE73 3205E5    STA        BUFSEC       ;DISK JOCKEY BUFFER EMPTY

```

```

DE76 320DE1      STA      BUFWRTN      ;SET BUFFER NOT DIRTY FLAG
DE79 3A0400      LDA      CDISK        ;JUMP TO CP/M WITH CURRENTLY SELECTED DISK IN C
DE7C 4F          MOV      C,A
DE7D 3AAADE      LDA      CWFLG
DE80 A7          ANA      A
DE81 11ACDE      LXI      D,COLDBEG      ;BEGINNING OF INITIAL COMMAND
DE84 3E0F        MVI      A,COLDEND-COLDBEG+1 ;LENGTH OF COMMAND
DE86 CA8EDE      JZ       CLDCMND
DE89 11BBDE      LXI      D,WARBEG
DE8C 3E01        MVI      A,WARMEND-WARBEG+1
DE8E 2108C7      CLDCMND LXI      H,CCP+8      ;COMMAND BUFFER
DE91 3207C7      STA      CCP+7
DE94 47          MOV      B,A
DE95 CDD4E1      CALL     MOVLOP
DE98 3AAADE      LDA      CWFLG
DE9B A7          ANA      A
DE9C 3AABDE      LDA      AUTOFLG
DE9F CAA3DE      JZ       CLDBOT
DEA2 1F          RAR
DEA3 1F          CLDBOT RAR
DEA4 DA00C7      JC       CCP
DEA7 C303C7      JMP      CCP+3      ;ENTER CP/M

DEAA 00          CWFLG  DB      0      ;COLD/WARM BOOT FLAG
    
```

```

*****
*
* THE FOLLOWING BYTE DETERMINES IF AN INITIAL COMMAND IS TO BE
* GIVEN TO CP/M ON WARM OR COLD BOOTS. THE VALUE OF THE BYTE IS
* USED TO GIVE THE COMMAND TO CP/M:
*
* 0 = NEVER GIVE COMMAND.
* 1 = GIVE COMMAND ON COLD BOOTS ONLY.
* 2 = GIVE THE COMMAND ON WARM BOOTS ONLY.
* 3 = GIVE THE COMMAND ON WARM AND COLD BOOTS.
*
*****
    
```

```

DEAB 01          AUTOFLG DB      1      ;AUTO COMMAND FEATURE
    
```

```

*****
*
* IF THERE IS A COMMAND INSERTED HERE, IT WILL BE GIVEN IF THE
* AUTO FEATURE IS ENABLED.
*   FOR EXAMPLE:
*
*   COLDBEG DB      'MBASIC MYPROG'
*   COLDEND DB      0
*
* WILL EXECUTE MICROSOFT BASIC, AND MBASIC WILL EXECUTE THE
* "MYPROG" BASIC PROGRAM.
*
*****
    
```

```

DEAC 5355424D49COLDBEG DB      'SUBMIT STARTUP';COLD BOOT COMMAND
DEBA 00          COLDEND DB      0
    
```

```

WARMBEG DB ' ' ;WARM BOOT COMMAND GOES HERE
DEBB 00 WARMEND DB 0
    
```

```

*****
*
* WBOOT LOADS IN ALL OF CP/M EXCEPT THE CBIOS, THEN INITIALIZES *
* SYSTEM PARAMETERS AS IN COLD BOOT. SEE THE COLD BOOT LOADER *
* LISTING FOR EXACTLY WHAT HAPPENS DURING WARM AND COLD BOOTS. *
*
*****
    
```

```

DEBC 310001 WBOOT LXI SP,TPA ;SET UP STACK POINTER
DEBF 3E01 MVI A,1
DEC0 = WFLG EQU $-1 ;TEST IF BEGINNING OR
DEC1 A7 ANA A ; ENDING A WARM BOOT
DEC2 3E01 MVI A,1
DEC4 32C0DE STA WFLG
DEC7 32AADE STA CWFLG ;SET COLD/WARM BOOT FLAG
DECA CA58DE JZ GOCPM
DECD AF XRA A
DECE 32C0DE STA WFLG
DED1 4F MOV C,A

IF (MAXHD NE 0) AND FIRST ;SUPPLY WARM BOOT FROM HARD DISK ?
LXI H,CCP-200H ;INITIAL DMA ADDRESS
PUSH H
STA HEAD
MVI A,4
PUSH PSW ;SAVE FIRST SECTOR
CALL HDDRV ;SELECT DRIVE A
MVI C,0
CALL HDTRK ;HOME THE DRIVE
WARMLOD POP PSW ;RESTORE SECTOR
POP H ;RESTORE DMA ADDRESS
INR A
STA HDSECTR
CPI 16 ;PAST BDOS ?
JZ WBOOT ;YES, ALL DONE
INR H ;UPDATE DMA ADDRESS
INR H
SHLD HDADD
PUSH H
PUSH PSW
WARMRD LXI B,RETRIES*100H+0 ;RETRY COUNTER
WRMREAD PUSH B ;SAVE THE RETRY COUNT
CALL HDREAD ;READ THE SECTOR
POP B
JNC WARMLOD ;TEST FOR ERROR
DCR B ;UPDATE THE ERROR COUNT
JNZ WRMREAD ;KEEP TRYING IF NOT TO MANY ERRORS
HLT ;CAN'T WARM BOOT
ENDIF

IF (MAXFLOP NE 0) AND NOT FIRST ;SUPPLY WARM BOOT FROM 2D ?
DED2 CD33DD CALL DJDRV ;SELECT DRIVE A
DED5 0E00 MVI C,0 ;SELECT SINGLE DENSITY
    
```

```

DED7 CD2DF4      CALL    DJDEN
DEDA 0E00        MVI     C,0           ;SELECT SIDE 0
DEDC CD30F4      CALL    DJSIDE
DEDF 3E0F        MVI     A,15          ;INITIALIZE THE SECTOR TO READ
DEE1 32FFDE      STA     NEWSEC
DEE4 2100C6      LXI     H,CCP-100H ;AND THE DMA ADDRESS
DEE7 221EDF      SHLD   NEWDMA
DEEA CDFEDE      CALL    WARMLOD      ;READ IN CP/M
DEED 0100CC      LXI     B,CCP+500H   ;LOAD ADDRESS FOR REST OF WARM BOOT
DEF0 CD12F4      CALL    DJDMA
DEF3 0E08        MVI     C,8
DEF5 CD0FF4      CALL    DJSEC
DEF8 CD32DF      CALL    WARMRD
DEFB C303CC      JMP     CCP+503H

DEFE 3E0F        WARMLOD MVI     A,15          ;PREVIOUS SECTOR
DEFF =          NEWSEC EQU     $-1
DF00 3C          INR     A           ;UPDATE THE PREVIOUS SECTOR
DF01 3C          INR     A
DF02 FE1B        CPI     27          ;WAS IT THE LAST ?
DF04 DA16DF      JC     NOWRAP
DF07 D609        SUI     9           ;YES
DF09 FE13        CPI     19
DF0B C8          RZ
DF0C 2A1EDF      LHLD   NEWDMA
DF0F 1180FB      LXI     D,-480H
DF12 19          DAD     D
DF13 221EDF      SHLD   NEWDMA
DF16 32FFDE      NOWRAP STA     NEWSEC      ;SAVE THE NEW SECTOR TO READ
DF19 4F          MOV     C,A
DF1A CD0FF4      CALL    DJSEC
DF1D 2100C6      LXI     H,CCP-100H   ;GET THE PREVIOUS DMA ADDRESS
DF1E =          NEWDMA EQU     $-2
DF20 110001      LXI     D,100H      ;UPDATE THE DMA ADDRESS
DF23 19          DAD     D
DF24 221EDF      SHLD   NEWDMA      ;SAVE THE DMA ADDRESS
DF27 44          MOV     B,H
DF28 4D          MOV     C,L
DF29 CD12F4      CALL    DJDMA      ;SET THE DMA ADDRESS
DF2C CD32DF      CALL    WARMRD
DF2F C3FEDE      JMP     WARMLOD

DF32 01000A      WARMRD LXI     B,RETRIES*100H+0;MAXIMUM # OF ERRORS
DF35 C5          WRMREAD PUSH    B
DF36 CD0CF4      CALL    DJTRK      ;SET THE TRACK
DF39 CD15F4      CALL    DJREAD     ;READ THE SECTOR
DF3C C1          POP     B
DF3D D0          RNC          ;CONTINUE IF SUCCESSFUL
DF3E 05          DCR     B
DF3F C235DF      JNZ    WRMREAD     ;KEEP TRYING
DF42 C32AF4      JMP     DJERR
                ENDIF

```

```

*****
*
* SETSEC JUST SAVES THE DESIRED SECTOR TO SEEK TO UNTIL AN
*
*****

```

* ACTUAL READ OR WRITE IS ATTEMPTED. *
* *

```
DF45 60 SETSEC MOV H,B
DF46 69 MOV L,C
DF47 22FDE4 SHLD CPMSEC
DF4A C9 DONOP RET
```

* *
* SETDMA SAVES THE DMA ADDRESS FOR THE DATA TRANSFER. *
* *

```
DF4B 60 SETDMA MOV H,B ;HL <- BC
DF4C 69 MOV L,C
DF4D 22EDE0 SHLD CPMDMA ;CP/M DMA ADDRESS
DF50 C9 RET
```

* *
* HOME IS TRANSLATED INTO A SEEK TO TRACK ZERO. *
* *

```
DF51 0E00 HOME MVI C,0 ;TRACK TO SEEK TO
```

* *
* SETTRK SAVES THE TRACK # TO SEEK TO. NOTHING IS DONE AT THIS *
* POINT, EVERYTHING IS DEFERRED UNTIL A READ OR WRITE. *
* *

```
DF53 79 SETTRK MOV A,C ;A <- TRACK #
DF54 3200E5 STA CPMTRK ;CP/M TRACK #
DF57 C9 RET
```

* *
* SECTRAN TRANSLATES A LOGICAL SECTOR # INTO A PHYSICAL SECTOR *
* #. *
* *

```
DF58 3AFFE4 IF (MAXHD NE 0) AND (MAXFLOP NE 0) ;BOTH TYPES ?
SECTRAN LDA CPMDRV ;GET THE DRIVE NUMBER
```

```
IF FIRST ;OVER THE # OF HARD DISKS ?
CPI MAXHD*LOGDSK
JC TRANHD
```

```
DF5B FE02 ELSE CPI MAXFLOP ;OVER THE # OF FLOPPIES ?
DF5D D28FDF JNC TRANHD
ENDIF
```


ENDIF

IF (MAXHD EQ 0) OR (MAXFLOP EQ 0) ;JUST ONE TYPE ?

SECTRAN EQU \$
ENDIF

IF MAXFLOP NE 0 ;FLOPPY TRANSLATION

```

DF60 03      TRANFP  INX      B
DF61 D5      PUSH     D          ;SAVE TABLE ADDRESS
DF62 C5      PUSH     B          ;SAVE SECTOR #
DF63 CD71E0  CALL     GETDPB      ;GET DPB ADDRESS INTO HL
DF66 7E      MOV      A,M       ;GET # OF CP/M SECTORS/TRACK
DF67 B7      ORA      A          ;CLEAR CARY
DF68 1F      RAR      A          ;DIVIDE BY TWO
DF69 91      SUB      C
DF6A F5      PUSH     PSW        ;SAVE ADJUSTED SECTOR
DF6B FA77DF  JM      SIDETWO
DF6E F1      SIDEA  POP      PSW  ;DISCARD ADJUSTED SECTOR
DF6F C1      POP      B          ;RESTORE SECTOR REQUESTED
DF70 D1      POP      D          ;RESTOR ADDRESS OF XLT TABLE
DF71 EB      SIDEONE XCHG      ;HL <- &(TRANSLATION TABLE)
DF72 09      DAD      B          ;BC = OFFSET INTO TABLE
DF73 6E      MOV      L,M       ;HL <- PHYSICAL SECTOR
DF74 2600    MVI      H,0
DF76 C9      RET

DF77 010F00  SIDETWO LXI      B,15      ;OFFSET TO SIDE BIT
DF7A 09      DAD      B
DF7B 7E      MOV      A,M
DF7C E608    ANI      8          ;TEST FOR DOUBLE SIDED
DF7E CA6EDF  JZ      SIDEA      ;MEDIA IS ONLY SINGLE SIDED
DF81 F1      POP      PSW        ;RETRIEVE ADJUSTED SECTOR
DF82 C1      POP      B
DF83 2F      CMA
DF84 3C      INR      A          ;MAKE SECTOR REQUEST POSITIVE
DF85 4F      MOV      C,A       ;MAKE NEW SECTOR THE REQUESTED SECTOR
DF86 D1      POP      D
DF87 CD71DF  CALL     SIDEONE
DF8A 3E80    MVI      A,80H      ;SIDE TWO BIT
DF8C B4      ORA      H          ; AND SECTOR
DF8D 67      MOV      H,A
DF8E C9      RET
    
```

ENDIF

IF MAXHD NE 0 ;HARD DISK TRANSLATION ROUTINE

```

DF8F 60      TRANHD  MOV      H,B
DF90 69      MOV      L,C
DF91 23      INX      H
DF92 C9      RET
    
```

ENDIF

*
* SETDRV SELECTS THE NEXT DRIVE TO BE USED IN READ/WRITE *
* OPERATIONS. IF THE DRIVE HAS NEVER BEEN SELECTED BEFORE, A *

```

* PARAMETER TABLE IS CREATED WHICH CORRECTLY DESCRIBES THE
* DISKETTE CURRENTLY IN THE DRIVE. DISKETTES CAN BE OF FOUR
* DIFFERENT SECTOR SIZES:
* 1) 128 BYTES SINGLE DENSITY.
* 2) 256 BYTES DOUBLE DENSITY.
* 3) 512 BYTES DOUBLE DENSITY.
* 4) 1024 BYTES DOUBLE DENSITY.
*
*****

```

```

DF93 79      SETDRV MOV    A,C          ;SAVE THE DRIVE #
DF94 32FFE4  STA    CPMDRV
DF97 FE05    CPI    MAXFLOP+(MAXHD*LOGDSK) ;CHECK FOR A VALID DRIVE #
DF99 D262E0  JNC    ZRET          ;ILLEGAL DRIVE #
DF9C 7B      MOV    A,E          ;TEST IF DRIVE EVER LOGGED IN BEFORE
DF9D E601    ANI    1
DF9F C249E0  JNZ    SETDRV1        ;BIT 0 OF E = 0 -> NEVER SELECTED BEFORE

                IF    (MAXHD NE 0) AND (MAXFLOP NE 0) ;BOTH TYPES ?
DFA2 3AFFE4  LDA    CPMDRV        ;GET THE DRIVE NUMBER

                IF    FIRST
                CPI    MAXHD*LOGDSK    ;OVER THE # OF HARD DISKS ?
                JC    DRVHD
                SUI    MAXHD*LOGDSK
                ELSE
DFA5 FE02    CPI    MAXFLOP        ;OVER THE # OF FLOPPIES ?
DFA7 D2FFDF  JNC    SUBFP
                ENDIF
                ENDIF

                IF    (MAXFLOP NE 0) AND FIRST
                MOV    C,A          ;SAVE DRIVE #
                MVI    A,0          ;HAVE THE FLOPPIES BEEN ACCESSED YET ?
FLOPFLG EQU  $-1
                ANA    A
                JNZ    FLOPOK
                MVI    B,17        ;FLOPPIES HAVN'T BEEN ACCESSED
                LXI    H,DJBOOT     ;CHECK IF 2D CONTROLLER IS INSTALLED
                MVI    A,(JMP)
                CLOPP CMP    M
                JNZ    ZRET
                DCR    B
                JNZ    CLOPP
                CALL   DJBOOT      ;INITIALIZE THE CONTROLLER
                MVI    A,1          ;SAVE 2D INITIALIZED FLAG
                STA    FLOPFLG
                ENDIF
                IF    MAXFLOP NE 0
DFAA 210100  FLOPOK LXI    H,1          ;SELECT SECTOR 1 OF TRACK 1
DFAD 2201E5  SHLD  TRUESEC
DFB0 3E01    MVI    A,1
DFB2 3200E5  STA    CPMTRK
DFB5 CD9EE1  CALL   FILL          ;FLUSH BUFFER AND REFILL
DFB8 DA62E0  JC    ZRET          ;TEST FOR ERROR RETURN
DFBB CD27F4  CALL   DJSTAT       ;GET STATUS ON CURRENT DRIVE

```

```

DFBE E60C      ANI      0CH      ;STRIP OFF UNWANTED BITS
DFC0 F5        PUSH     PSW      ;USED TO SELECT A DPB
DFC1 1F        RAR
DFC2 218AE0    LXI      H,XLTS    ;TABLE OF XLT ADDRESSES
DFC5 5F        MOV      E,A
DFC6 1600      MVI      D,0
DFC8 19        DAD      D
DFC9 E5        PUSH     H      ;SAVE POINTER TO PROPER XLT
DFCA CD71E0    CALL    GETDPB   ;GET DPH POINTER INTO DE
DFCD EB        XCHG
DFCE D1        POP      D
DFCF 0602      MVI      B,2      ;NUMBER OF BYTES TO MOVE
DFD1 CDD4E1    CALL    MOVLOP   ;MOVE THE ADDRESS OF XLT
DFD4 110800    LXI      D,8      ;OFFSET TO DPB POINTER
DFD7 19        DAD      D      ;HL <- &DPH.DPB
DFD8 E5        PUSH     H
DFD9 2A07F0    LHLD    ORIGIN+7 ;GET ADDRESS OF DJ TERMINAL OUT ROUTINE
DFDC 23        INX      H      ;BUMP TO LOOK AT ADDRESS OF
;             UART STATUS LOCATION

DFDD 7E        MOV      A,M
DFDE EE03      XRI      3      ;ADJUST FOR PROPER REV DJ
DFE0 6F        MOV      L,A
DFE1 26F3      MVI      H,(ORIGIN+300H)/100H
DFE3 7E        MOV      A,M
DFE4 E608      ANI      DBLSID   ;CHECK DOUBLE SIDED BIT
DFE6 11FDE3    LXI      D,DPB128S ;BASE FOR SINGLE SIDED DPB'S
DFE9 C2EFDf    JNZ     SIDEOK
DFEC 113DE4    LXI      D,DPB128D ;BASE OF DOUBLE SIDED DPB'S
DFEF EB        XCHG    SIDEOK ;HL <- DBP BASE, DE <- &DPH.DPB
DFF0 D1        POP      D      ;RESTORE DE (POINTER INTO DPH)
DFF1 F1        POP      PSW   ;OFFSET TO CORRECT DPB
DFF2 17        RAL
DFF3 17        RAL
DFF4 4F        MOV      C,A
DFF5 0600      MVI      B,0
DFF7 09        DAD      B
DFF8 EB        XCHG    ;PUT DPB ADDRESS IN DPH
DFF9 73        MOV      M,E
DFFA 23        INX      H
DFFB 72        MOV      M,D
                ENDIF

DFFC C349E0    IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
                JMP     SETDRV1 ;SKIP OVER THE HARD DISK SELECT
                IF      NOT FIRST
DFFF D602      SUBFP   SUI     MAXFLOP ;ADJUST THE DRIVE #
                ENDIF
                ENDIF

E001 CD68E0    DRVHD  CALL    DIVLOG ;DIVIDE BY LOGICAL DISKS PER DRIVE
E004 79        MOV      A,C
E005 322AE3    STA     HDDISK
E008 CD18E3    CALL    DRVPTR
E00B 7E        MOV      A,M
E00C 3C        INR     A

```

```

E00D C249E0      JNZ      SETDRV1
E010 F6FC        ORI      NULL          ;SELECT DRIVE
E012 D352        OUT      HDFUNC
E014 3E05        MVI      A,SCENBL      ;ENABLE THE CONTROLLER
E016 D350        OUT      HDCNTL
E018 0EEF        MVI      C,239        ;WAIT APPROX 2 MINUTES FOR DISK TO READY
E01A 210000      LXI      H,0
E01D 2B          TDELAY  DCX      H
E01E 7C          MOV      A,H
E01F B5          ORA      L
E020 CC66E0      CZ      DCRC
E023 C8          RZ
E024 DB50        IN      HDSTAT      ;TEST IF READY YET
E026 E620        ANI      DRVRDY
E028 C21DE0      JNZ      TDELAY

                IF      SDELAY
E02B 210000      LXI      H,0          ;TIME ONE REVOLUTION OF THE DRIVE
E02E 0E40        MVI      C,INDEX
E030 DB50        IN      HDSTAT
E032 A1          ANA      C
E033 47          MOV      B,A          ;SAVE CURRENT INDEX LEVEL IN B
E034 DB50        INDX1  IN      HDSTAT
E036 A1          ANA      C
E037 B8          CMP      B          ;LOOP UTIL INDEX LEVEL CHANGES
E038 CA34E0      JZ      INDX1
E03B 23          INDX2  INX      H
E03C DB50        IN      HDSTAT      ;START COUNTING UNTIL INDEX RETURNS TO
E03E A1          ANA      C          ;      PREVIOUS STATE
E03F B8          CMP      B
E040 C23BE0      JNZ      INDX2
                IF      M10
                DAD      H
                ENDDIF
E043 2210E2      SHLD   SETTLE      ;SAVE THE COUNT FOR TIMEOUT DELAY
                ENDDIF
E046 CDFAE1      CALL   HDHOME

E049 CD71E0      SETDRV1 CALL  GETDPB      ;GET ADDRESS OF DPB IN HL
E04C 010F00      LXI      B,15      ;OFFSET TO SECTOR SIZE
E04F 09          DAD      B
E050 7E          MOV      A,M          ;GET SECTOR SIZE
E051 E607        ANI      7H
E053 329EE0      STA      SECSIZ
E056 7E          MOV      A,M
E057 1F          RAR
E058 1F          RAR
E059 1F          RAR
E05A 1F          RAR
E05B E60F        ANI      0FH
E05D 32DCE0      STA      SECPSEC
E060 EB          XCHG      ;HL <- DPH
E061 C9          RET

E062 210000      ZRET   LXI      H,0          ;SELDRV ERROR EXIT

```

```

E065 C9          RET

E066 0D          DCRC      IF      MAXHD NE 0
E067 C9          RET          C          ;CONDITIONAL DECREMENT C ROUTINE

E068 0E00        DIVLOG   MVI      C,0
E06A D603        DIVLOGX  SUI      LOGDSK
E06C D8          RC
E06D 0C          INR       C
E06E C36AE0      JMP       DIVLOGX
                    ENDIF
    
```

```

*****
*
* GETDPB RETURNS HL POINTING TO THE DPB OF THE CURRENTLY
* SELECTED DRIVE, DE POINTING TO DPH.
*
*****
    
```

```

E071 3AFFE4      GETDPB   LDA      CPMDRV
E074 6F          MOV      L,A          ;FORM OFFSET
E075 2600        MVI      H,0
E077 29          DAD      H
E078 29          DAD      H
E079 29          DAD      H
E07A 29          DAD      H
E07B 11ADE4      LXI      D,DPBASE   ;BASE OF DPH'S
E07E 19          DAD      D
E07F E5          PUSH     H          ;SAVE ADDRESS OF DPH
E080 110A00      LXI      D,10        ;OFFSET TO DPB
E083 19          DAD      D
E084 7E          MOV      A,M          ;GET LOW BYTE OF DPB ADDRESS
E085 23          INX      H
E086 66          MOV      H,M          ;GET LOW BYTE OF DPB
E087 6F          MOV      L,A
E088 D1          POP      D
E089 C9          RET
    
```

```

*****
*
* XLTS IS A TABLE OF ADDRESS THAT POINT TO EACH OF THE XLT
* TABLES FOR EACH SECTOR SIZE.
*
*****
    
```

```

E08A 2FE3        XLTS     IF      MAXFLOP NE 0
E08C 4AE3        DW      XLT128     ;XLT FOR 128 BYTE SECTORS
E08E 7FE3        DW      XLT256     ;XLT FOR 256 BYTE SECTORS
E090 BCE3        DW      XLT512     ;XLT FOR 512 BYTE SECTORS
                    DW      XLT124     ;XLT FOR 1024 BYTE SECTORS
                    ENDIF
    
```

```

*****
*
* WRITE ROUTINE MOVES DATA FROM MEMORY INTO THE BUFFER. IF THE
*
*****
    
```

```
* DESIRED CP/M SECTOR IS NOT CONTAINED IN THE DISK BUFFER, THE *
* BUFFER IS FIRST FLUSHED TO THE DISK IF IT HAS EVER BEEN *
* WRITTEN INTO, THEN A READ IS PERFORMED INTO THE BUFFER TO GET *
* THE DESIRED SECTOR. ONCE THE CORRECT SECTOR IS IN MEMORY, THE *
* BUFFER WRITTEN INDICATOR IS SET, SO THE BUFFER WILL BE *
* FLUSHED, THEN THE DATA IS TRANSFERRED INTO THE BUFFER. *
*
```

```
E092 79 WRITE MOV A,C ;SAVE WRITE COMMAND TYPE
E093 3204E1 STA WRITTP
E096 3E01 MVI A,1 ;SET WRITE COMMAND
E098 06 DB (MVI) OR (B*8) ;THIS "MVI B" INSTRUCTION CAUSES
; THE FOLLOWING "XRA A" TO
; BE SKIPPED OVER.
```

```
* READ ROUTINE TO BUFFER DATA FROM THE DISK. IF THE SECTOR *
* REQUESTED FROM CP/M IS IN THE BUFFER, THEN THE DATA IS SIMPLY *
* TRANSFERRED FROM THE BUFFER TO THE DESIRED DMA ADDRESS. IF *
* THE BUFFER DOES NOT CONTAIN THE DESIRED SECTOR, THE BUFFER IS *
* FLUSHED TO THE DISK IF IT HAS EVER BEEN WRITTEN INTO, THEN *
* FILLED WITH THE SECTOR FROM THE DISK THAT CONTAINS THE *
* DESIRED CP/M SECTOR. *
*
```

```
E099 AF READ XRA A ;SET THE COMMAND TYPE TO READ
E09A 32F0E0 STA RDWR ;SAVE COMMAND TYPE
```

```
* REDWRT CALCULATES THE PHYSICAL SECTOR ON THE DISK THAT *
* CONTAINS THE DESIRED CP/M SECTOR, THEN CHECKS IF IT IS THE *
* SECTOR CURRENTLY IN THE BUFFER. IF NO MATCH IS MADE, THE *
* BUFFER IS FLUSHED IF NECESSARY AND THE CORRECT SECTOR READ *
* FROM THE DISK. *
*
```

```
E09D 0600 REDWRT MVI B,0 ;THE 0 IS MODIFIED TO CONTAIN THE LOG2
E09E = SECSIZ EQU $-1 ; OF THE PHYSICAL SECTOR SIZE/128
; ON THE CURRENTLY SELECTED DISK.
E09F 2AFDE4 LHLD CPMSEC ;GET THE DESIRED CP/M SECTOR #
E0A2 7C MOV A,H
E0A3 E680 ANI 80H ;SAVE ONLY THE SIDE BIT
E0A5 4F MOV C,A ;REMEMBER THE SIDE
E0A6 7C MOV A,H
E0A7 E67F ANI 7FH ;FORGET THE SIDE BIT
E0A9 67 MOV H,A
E0AA 2B DCX H ;TEMPORARY ADJUSTMENT
E0AB 05 DIVLOOP DCR B ;UPDATE REPEAT COUNT
E0AC CAB9E0 JZ DIVDONE
E0AF B7 ORA A
E0B0 7C MOV A,H
```

```

E0B1 1F          RAR
E0B2 67          MOV      H,A
E0B3 7D          MOV      A,L
E0B4 1F          RAR          ;DIVIDE THE CP/M SECTOR # BY THE SIZE
                                ;      OF THE PHYSICAL SECTORS

E0B5 6F          MOV      L,A
E0B6 C3ABE0      JMP      DIVLOOP      ;
E0B9 23          DIVDONE INX      H
E0BA 7C          MOV      A,H
E0BB B1          ORA      C          ;RESTORE THE SIDE BIT
E0BC 67          MOV      H,A
E0BD 2201E5      SHLD     TRUESEC      ;SAVE THE PHYSICAL SECTOR NUMBER
E0C0 21FFE4      LXI      H,CPMDRV      ;POINTER TO DESIRED DRIVE,TRACK, AND SECTOR
E0C3 1103E5      LXI      D,BUFDRV      ;POINTER TO BUFFER DRIVE,TRACK, AND SECTOR
E0C6 0605        MVI      B,5          ;COUNT LOOP
E0C8 05          DTSLOP  DCR      B          ;TEST IF DONE WITH COMPARE
E0C9 CAD7E0      JZ       MOVE      ;YES, MATCH. GO MOVE THE DATA
E0CC 1A          LDAX    D          ;GET A BYTE TO COMPARE
E0CD BE          CMP      M          ;TEST FOR MATCH
E0CE 23          INX      H          ;BUMP POINTERS TO NEXT DATA ITEM
E0CF 13          INX      D
E0D0 CAC8E0      JZ       DTSLOP      ;MATCH, CONTINUE TESTING
    
```

```

*****
*
* DRIVE, TRACK, AND SECTOR DON'T MATCH, FLUSH THE BUFFER IF
* NECESSARY AND THEN REFILL.
*
*****
    
```

```

E0D3 CD9EE1      CALL     FILL          ;FILL THE BUFFER WITH CORRECT PHYSICAL SECTOR
E0D6 D8          RC          ;NO GOOD, RETURN WITH ERROR INDICATION
    
```

```

*****
*
* MOVE HAS BEEN MODIFIED TO CAUSE EITHER A TRANSFER INTO OR OUT
* THE BUFFER.
*
*****
    
```

```

E0D7 3AFDE4      MOVE     LDA      CPMSEC      ;GET THE CP/M SECTOR TO TRANSFER
E0DA 3D          DCR      A          ;ADJUST TO PROPER SECTOR IN BUFFER
E0DB E600        ANI      0          ;STRIP OFF HIGH ORDERED BITS
E0DC =          SECPSEC EQU    $-1      ;THE 0 IS MODIFIED TO REPRESENT THE # OF
                                ;      CP/M SECTORS PER PHYSICAL SECTORS
E0DD 6F          MOV      L,A          ;PUT INTO HL
E0DE 2600        MVI      H,0
E0E0 29          DAD      H          ;FORM OFFSET INTO BUFFER
E0E1 29          DAD      H
E0E2 29          DAD      H
E0E3 29          DAD      H
E0E4 29          DAD      H
E0E5 29          DAD      H
E0E6 29          DAD      H
E0E7 1107E5      LXI      D,BUFFER      ;BEGINNING ADDRESS OF BUFFER
E0EA 19          DAD      D          ;FORM BEGINNING ADDRESS OF SECTOR TO TRANSFER
    
```

```

E0EB EB          XCHG          ;DE = ADDRESS IN BUFFER
E0EC 210000      LXI          H,0      ;GET DMA ADDRESS, THE 0 IS MODIFIED TO
;          CONTAIN THE DMA ADDRESS

E0ED =          CPMDMA EQU     $-2
E0EF 3E00        MVI          A,0      ;THE ZERO GETS MODIFIED TO CONTAIN
;          A ZERO IF A READ, OR A 1 IF WRITE

E0F0 =          RDWR EQU     $-1
E0F1 A7          ANA          A        ;TEST WHICH KIND OF OPERATION
E0F2 C2FAE0      JNZ          INTO     ;TRANSFER DATA INTO THE BUFFER
E0F5 CDD2E1      OUTOF CALL    MOVER
E0F8 AF          XRA          A
E0F9 C9          RET

E0FA EB          INTO XCHG          ;
E0FB CDD2E1      CALL    MOVER      ;MOVE THE DATA, HL = DESTINATION
;          DE = SOURCE

E0FE 3E01        MVI          A,1
E100 320DE1      STA          BUFWRN  ;SET BUFFER WRITTEN INTO FLAG
E103 3E00        MVI          A,0      ;CHECK FOR DIRECTORY WRITE
E104 =          WRITTP EQU     $-1
E105 3D          DCR          A
E106 3E00        MVI          A,0
E108 3204E1      STA          WRITTP  ;SET NO DIRECTORY WRITE
E10B C0          RNZ          ;NO ERROR EXIT
    
```

```

*****
*
* FLUSH WRITES THE CONTENTS OF THE BUFFER OUT TO THE DISK IF
* IT HAS EVER BEEN WRITTEN INTO.
*
*****
    
```

```

E10C 3E00        FLUSH MVI      A,0      ;THE 0 IS MODIFIED TO REFLECT IF
;          THE BUFFER HAS BEEN WRITTEN INTO

E10D =          BUFWRN EQU     $-1
E10E A7          ANA          A        ;TEST IF WRITTEN INTO
E10F C8          RZ          ;NOT WRITTEN, ALL DONE
    
```

```

E110 2118F4      LXI          H,DJWRITE ;WRITE OPERATION FOR DISK JOCKEY
E113 119AE2      LXI          D,HDWRITE ;WRITE OPERATION FOR HARD DISK
E116 CDE1E1      CALL    DECIDE
ELSE
IF MAXHD NE 0 AND (MAXFLOP NE 0)
LXI H,HDWRITE
ENDIF
IF MAXFLOP NE 0
LXI H,DJWRITE
ENDIF
ENDIF
    
```

```

*****
*
* PREP PREPARES TO READ/WRITE THE DISK. RETRIES ARE ATTEMPTED.
* UPON ENTRY, H&L MUST CONTAIN THE READ OR WRITE OPERATION
* ADDRESS.
*
*****
    
```



```

*
*****
E119 AF      PREP   XRA      A           ;RESET BUFFER WRITTEN FLAG
E11A 320DE1  STA      BUFWRTN
E11D 227FE1  SHLD     RETRYOP    ;SET UP THE READ/WRITE OPERATION
E120 060A    MVI      B,RETRIES ;MAXIMUM NUMBER OF RETRIES TO ATTEMPT
E122 C5      RETRYLP  PUSH     B           ;SAVE THE RETRY COUNT
E123 3A03E5  LDA      BUFDRV    ;GET DRIVE NUMBER INVOLVED IN THE OPERATION

                IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
                IF      FIRST
                CPI      MAXHD*LOGDSK
                JC      NOADJST
                SUI      MAXHD*LOGDSK
                ELSE
E126 FE02    CPI      MAXFLOP
E128 DA2DE1  JC      NOADJST
E12B D602    SUI      MAXFLOP
                ENDIF

E12D 4F      NOADJST  MOV      C,A
E12E 2133DD  LXI      H,DJDRV   ;SELECT DRIVE
E131 11E9E1  LXI      D,HDRV
E134 CDDDE1  CALL     DECIDGO
                ELSE
                MOV      C,A
                IF      MAXHD NE 0
                CALL     HDDRV
                ENDIF
                IF      MAXFLOP NE 0
                CALL     DJDRV   ;SELECT THE DRIVE
                ENDIF
                ENDIF

E137 3A04E5  LDA      BUFTRK
E13A A7      ANA      A           ;TEST FOR TRACK ZERO
E13B 4F      MOV      C,A
E13C C5      PUSH     B

                IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E13D 2109F4  LXI      H,DJHOME
E140 11FAE1  LXI      D,HDHOME
E143 CCDDE1  CZ      DECIDGO
                ELSE
                IF      MAXHD NE 0
                CZ      HDHOME
                ENDIF
                IF      MAXFLOP NE 0
                CZ      DJHOME   ;HOME THE DRIVE IF TRACK 0
                ENDIF
                ENDIF

E146 C1      POP      B           ;RESTORE TRACK #

                IF      (MAXHD NE 0) AND (MAXFLOP NE 0)

```

```

E147 210CF4      LXI      H,DJTRK
E14A 111BE2      LXI      D,HDTRK
E14D CDDDE1      CALL     DECIDGO
                  ELSE
                  IF      MAXHD NE 0
                  CALL     HDTRK
                  ENDIF
                  IF      MAXFLOP NE 0
                  CALL     DJTRK          ;SEEK TO PROPER TRACK
                  ENDIF
                  ENDIF

E150 2A05E5      LHL     BUFSEC
E153 7C          MOV     A,H          ;GET SECTOR INVOLVED IN OPERATION
E154 07          RLC          ;BIT 0 OF A EQUALS SIDE #
E155 E601        ANI     1          ;STRIP OFF UNNECESSARY BITS
E157 4F          MOV     C,A          ;C <- SIDE #

                  IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E158 2130F4      LXI      H,DJSIDE
E15B 1147E2      LXI      D,HDSIDE
E15E CDDDE1      CALL     DECIDGO
                  ELSE
                  IF      MAXHD NE 0
                  CALL     HDSIDE
                  ENDIF
                  IF      MAXFLOP NE 0
                  CALL     DJSIDE          ;SELECT THE SIDE
                  ENDIF
                  ENDIF

E161 2A05E5      LHL     BUFSEC
E164 7C          MOV     A,H
E165 E67F        ANI     7FH          ;STRIP OFF SIDE BIT
E167 47          MOV     B,A          ;C <- SECTOR #
E168 4D          MOV     C,L

                  IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E169 210FF4      LXI      H,DJSEC
E16C 1150E2      LXI      D,HDSEC
E16F CDDDE1      CALL     DECIDGO
                  ELSE
                  IF      MAXHD NE 0
                  CALL     HDSEC
                  ENDIF
                  IF      MAXFLOP NE 0
                  CALL     DJSEC          ;SELECT THE SIDE
                  ENDIF
                  ENDIF

E172 0107E5      LXI      B,BUFFER          ;SET THE DMA ADDRESS

                  IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E175 2112F4      LXI      H,DJDMA
E178 1142E2      LXI      D,HDDMA
E17B CDDDE1      CALL     DECIDGO

```

```

ELSE
IF      MAXHD NE 0
CALL    HDDMA
ENDIF
IF      MAXFLOP NE 0
CALL    DJDMA          ;SELECT THE SIDE
ENDIF
ENDIF

```

```

E17E CD0000      CALL    0          ;GET OPERATION ADDRESS
E17F =          RETRYOP EQU    $-2
E181 C1          POP     B          ;RESTORE THE RETRY COUNTER
E182 3E00        MVI     A,0       ;NO ERROR EXIT STATUS
E184 D0          RNC           ;RETURN NO ERROR
E185 05          DCR     B          ;UPDATE THE RETRY COUNTER
E186 37          STC           ;ASSUME RETRY COUNT EXPIRED
E187 3EFF        MVI     A,0FFH    ;ERROR RETURN
E189 C8          RZ
E18A 78          MOV     A,B
E18B FE05        CPI     RETRIES/2
E18D C222E1      JNZ     RETRYLP    ;TRY AGAIN

```

```

E190 C5          PUSH    B
IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E191 2109F4      LXI     H,DJHOME
E194 11FAE1      LXI     D,HDHOME
E197 CDDDE1      CALL    DECIDGO
ELSE
IF      MAXHD NE 0
CALL    HDHOME
ENDIF
IF      MAXFLOP NE 0
CALL    DJHOME          ;HOME THE DRIVE IF TRACK 0
ENDIF
ENDIF

```

```

E19A C1          POP     B
E19B C322E1      JMP     RETRYLP

```

```

*****
*
* FILL FILLS THE BUFFER WITH A NEW SECTOR FROM THE DISK.
*
*****

```

```

E19E CD0CE1      FILL   CALL    FLUSH          ;FLUSH BUFFER FIRST
E1A1 D8          RC          ;CHECK FOR ERROR
E1A2 11FFE4      LXI     D,CPMDRV        ;UPDATE THE DRIVE, TRACK, AND SECTOR
E1A5 2103E5      LXI     H,BUFDRV
E1A8 0604        MVI     B,4          ;NUMBER OF BYTES TO MOVE
E1AA CDD4E1      CALL    MOVLOP         ;COPY THE DATA

E1AD 3AF0E0      LDA     RDWR
E1B0 A7          ANA     A
E1B1 CAC6E1      JZ     FREAD
E1B4 3A04E1      LDA     WRITTP

```

```

E1B7 3D      DCR      A
E1B8 3D      DCR      A
E1B9 C8      RZ
E1BA CD71E0  CALL     GETDPB
E1BD 110F00  LXI      D,15
E1C0 19      DAD      D
E1C1 7E      MOV      A,M
E1C2 E603    ANI      3
E1C4 3D      DCR      A
E1C5 C8      RZ
    
```

```

E1C6 =      FREAD    EQU      $
                IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E1C6 2115F4  LXI      H,DJREAD
E1C9 1165E2  LXI      D,HDREAD
E1CC CDE1E1  CALL     DECIDE
                ELSE
                IF      MAXHD NE 0
                LXI      H,HDREAD
                ENDIF
                IF      MAXFLOP NE 0
                LXI      H,DJREAD          ;SELECT THE SIDE
                ENDIF
                ENDIF
E1CF C319E1  JMP      PREP          ;SELECT DRIVE, TRACK, AND SECTOR.
                                ; THEN READ THE BUFFER
    
```

```

*****
*
* MOVER MOVES 128 BYTES OF DATA. SOURCE POINTER IN DE, DEST
* POINTER IN HL.
*
*****
    
```

```

E1D2 0680    MOVER    MVI      B,128          ;LENGTH OF TRANSFER
E1D4 1A      MOVLOP   LDAX     D          ;GET A BTE OF SOURCE
E1D5 77      MOV      M,A          ;MOVE IT
E1D6 13      INX      D          ;BUMP POINTERS
E1D7 23      INX      H
E1D8 05      DCR      B          ;UPDATE COUNTER
E1D9 C2D4E1  JNZ     MOVLOP   ;CONTINUE MOVING UNTIL DONE
E1DC C9      RET
    
```

```

*****
*
* ROUTINES TO DECIDE WHICH CONTROLLER TO USE.
*
*****
    
```

```

E1DD CDE1E1  DECIDGO  CALL     DECIDE ;WHICH CONTROLLER ?
E1E0 E9      PCHL
                ENDIF

E1E1 3A03E5  DECIDE   LDA      BUFDRV          ;GET PROPER ROUTINE INTO H&L, BASED
                IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
    
```

```

                IF      FIRST      ;   ON CURRENTLY SELECTED DRIVE
                CPI     MAXHD*LOGDSK
                RNC
                ELSE
E1E4 FE02      CPI     MAXFLOP
E1E6 D8        RC
                ENDIF
E1E7 EB        XCHG
E1E8 C9        RET
                ENDIF

```

```

*****
*
* THE FOLLOWING IS THE EQUIVALENT OF THE LOWEST LEVEL DRIVERS
* FOR THE HARD DISK.
*
*****

```

```

E1E9 79      HDDRV  IF      MAXHD NE 0
E1EA CD68E0  MOV     A,C      ;SELECT HARD DISK DRIVE
E1ED 79      CALL    DIVLOG   ;GET THE PHYSICAL DRIVE #
E1EE 322AE3  MOV     A,C
E1F1 F6FC    STA     HDDISK   ;SELECT THE DRIVE
E1F3 D352    ORI     NULL
E1F5 3E0F    OUT    HDFUNC
E1F7 D350    MVI    A,WENABL
E1F9 C9      OUT    HDCNTL
                RET

```

```

E1FA CD18E3  HDHOME CALL   DRVPTR
E1FD 3600    MVI    M,0      ;SET TRACK TO ZERO

```

```

E1FF DB50    STEPO  IF      SDELAY
E201 E601    IN     HDSTAT   ;TEST STATUS
E203 CA0FE2  ANI    TKZERO   ;AT TRACK ZERO ?
E206 3E01    JZ     DELAY
E208 37      MVI    A,1
E209 CD2FE2  STC
E20C C3FFE1  CALL   ACCOK     ;TAKE ONE STEP OUT
                JMP    STEPO

```

```
ELSE
```

```

                IN     HDSTAT
                ANI    TKZERO
                RZ
                XRA   A
                JMP   ACCOK
                ENDIF

```

```

E20F 210000  DELAY  IF      SDELAY
E210 =       LXI   H,0      ;GET DELAY
E212 2B     SETTLE EQU    $-2
E213 7C     DELOOP DCX   H      ;WAIT 20MS
E214 B5     MOV   A,H
                ORA   L

```

```

E215 23      INX      H
E216 2B      DCX      H
E217 C212E2  JNZ      DELOOP
E21A C9      RET
                ENDIF

E21B CD18E3  HDTRK  CALL    DRVPTR      ;GET POINTER TO CURRENT TRACK
E21E 5E      MOV    E,M          ;GET CURRENT TRACK
E21F 71      MOV    M,C          ;UPDATE THE TRACK
E220 7B      MOV    A,E          ;NEED TO SEEK AT ALL ?
E221 91      SUB    C
E222 C8      RZ
E223 3F      CMC          ;GET CARRY INTO DIRECTION
E224 DA29E2  JC     HDTRK2
E227 2F      CMA
E228 3C      INR    A
                IF    NOT SDELAY
HDTRK2  JMP    ACCOK
                ELSE
E229 CD2FE2  HDTRK2  CALL    ACCOK
E22C C30FE2  JMP    DELAY
                ENDIF

E22F 47      ACCOK  MOV    B,A          ;PREP FOR BUILD
E230 CD23E3  CALL   BUILD
E233 E6FB    SLOOP  ANI    NSTEP      ;GET STEP PULSE LOW
E235 D352    OUT   HDFUNC      ;OUTPUT LOW STEP LINE
E237 F604    ORI   PSTEP      ;SET STEP LINE HIGH
E239 D352    OUT   HDFUNC      ;OUTPUT HIGH STEP LINE
E23B 05      DCR   B          ;UPDATE REPEAT COUNT
E23C C233E2  JNZ   SLOOP      ;KEEP GOING THE REQUIRED # OF TRACKS
E23F C348E2  JMP   WSDONE

E242 60      HDDMA  MOV    H,B          ;SAVE THE DMA ADDRESS
E243 69      MOV    L,C
E244 227FE2  SHLD  HDADD
E247 =      HDSIDE EQU    $
E247 C9      RET

E248 DB50    WSDONE  IN     HDSTAT      ;WAIT FOR SEEK COMPLETE TO FINISH
E24A E604    ANI   COMPLT
E24C CA48E2  JZ    WSDONE
E24F C9      RET

                IF    M26
E250 3E1F    HDSEC  MVI   A,01FH    ;FOR COMPATIBILITY WITH CBIOS REV 2.3, 2.4
E252 A1      ANA   C
E253 CC62E2  CZ    GETSPT
E256 3208E3  STA   HDSECTR
E259 3EE0    MVI   A,0E0H
E25B A1      ANA   C
E25C 07      RLC
E25D 07      RLC
E25E 07      RLC
E25F 3224E3  STA   HEAD
E262 3E20    GETSPT MVI   A,HDSPT

```

```

E264 C9          RET
                ELSE
                HDSEC  MOV    A,C
                  CALL   DIVSPT
                  ADI    HDSPT
                  ANA    A
                  CZ     GETSPT
                  STA    HDSECTR
                  MOV    A,C
                  STA    HEAD
                GETSPT MVI    A,HDSPT
                  DCR    C
                  RET

                DIVSPT MVI    C,0
                DIVSPTX SUI   HDSPT
                  RC
                  INR    C
                  JMP    DIVSPTX
                ENDIF

E265 CDE3E2     HDREAD CALL   HDPREP
E268 D8         RC
E269 AF         XRA    A
E26A D351      OUT    HDCMND
E26C 2F        CMA
E26D D353      OUT    HDDATA
E26F D353      OUT    HDDATA
E271 3E01      MVI    A,RSECT      ;READ SECTOR COMMAND
E273 D351      OUT    HDCMND
E275 CDC9E2    CALL   PROCESS
E278 D8         RC
E279 AF         XRA    A
E27A D351      OUT    HDCMND
E27C 0680      MVI    B,SECLN/4
E27E 210000    LXI    H,0
E27F =         HDADD  EQU    $-2
E281 DB53      IN     HDDATA
E283 DB53      IN     HDDATA
E285 DB53      RTLOOP IN     HDDATA      ;MOVE FOUR BYTES
E287 77        MOV    M,A
E288 23        INX   H
E289 DB53      IN     HDDATA
E28B 77        MOV    M,A
E28C 23        INX   H
E28D DB53      IN     HDDATA
E28F 77        MOV    M,A
E290 23        INX   H
E291 DB53      IN     HDDATA
E293 77        MOV    M,A
E294 23        INX   H
E295 05        DCR    B
E296 C285E2    JNZ    RTLOOP
E299 C9        RET
    
```

```

E29A CDE3E2   HDWRITE CALL   HDPREP           ;PREPARE HEADER
E29D D8       RC
E29E AF       XRA      A
E29F D351     OUT      HDCMND
E2A1 2A7FE2   LHLD     HDADD
E2A4 0680     MVI      B,SECLN/4
E2A6 7E       WTLOOP  MOV      A,M           ;MOVE 4 BYTES
E2A7 D353     OUT      HDDATA
E2A9 23       INX     H
E2AA 7E       MOV      A,M
E2AB D353     OUT      HDDATA
E2AD 23       INX     H
E2AE 7E       MOV      A,M
E2AF D353     OUT      HDDATA
E2B1 23       INX     H
E2B2 7E       MOV      A,M
E2B3 D353     OUT      HDDATA
E2B5 23       INX     H
E2B6 05       DCR     B
E2B7 C2A6E2   JNZ     WTLOOP
E2BA 3E05     MVI      A,WSECT   ;ISSUE WRITE SECTOR COMMAND
E2BC D351     OUT      HDCMND
E2BE CDC9E2   CALL    PROCESS
E2C1 D8       RC
E2C2 3E10     MVI      A,WFAULT
E2C4 A0       ANA     B
E2C5 37       STC
E2C6 C8       RZ
E2C7 AF       XRA     A
E2C8 C9       RET

E2C9 DB50     PROCESS  IN      HDSTAT           ;WAIT FOR COMMAND TO FINISH
E2CB 47       MOV     B,A
E2CC E602     ANI     OPDONE
E2CE CAC9E2   JZ      PROCESS
E2D1 3E07     MVI     A,DSKCLK
E2D3 D350     OUT     HDCNTL
E2D5 DB50     IN      HDSTAT
E2D7 E608     ANI     TMOUT       ;TIMED OUT ?
E2D9 37       STC
E2DA C0       RNZ
E2DB DB51     IN      HDRESLT
E2DD E602     ANI     RETRY       ;ANY RETRIES ?
E2DF 37       STC
E2E0 C0       RNZ
E2E1 AF       XRA     A
E2E2 C9       RET

E2E3 DB50     HDPREP  IN      HDSTAT
E2E5 E620     ANI     DRVRDY
E2E7 37       STC
E2E8 C0       RNZ
E2E9 3E08     MVI     A,ISBUFF   ;INITIALIZE POINTER
E2EB D351     OUT     HDCMND
E2ED CD23E3   CALL    BUILD

```



```

E2F0 F60C      ORI      0CH
E2F2 D352      OUT      HDFUNC
E2F4 3A24E3    LDA      HEAD
E2F7 D353      OUT      HDDATA      ;FORM HEAD BYTE
E2F9 CD18E3    CALL     DRVPTR
E2FC 7E        MOV      A,M          ;FORM TRACK BYTE
E2FD D353      OUT      HDDATA
E2FF A7        ANA      A
E300 0680      MVI      B,80H
E302 CA07E3    JZ       ZKEY
E305 0600      MVI      B,0
E307 3E00      MVI      A,0          ;FORM SECTOR BYTE
E308 =        HDSECTR EQU    $-1
E309 D353      OUT      HDDATA
E30B 78        MOV      A,B
E30C D353      OUT      HDDATA
E30E 3E07      MVI      A,DSKCLK
E310 D350      OUT      HDCNTL
E312 3E0F      MVI      A,WENABL
E314 D350      OUT      HDCNTL
E316 AF        XRA      A
E317 C9        RET

```

```

E318 2A2AE3    DRVPTR  LHLD     HDDISK
E31B EB        XCHG
E31C 1600      MVI      D,0
E31E 212EE3    LXI      H,DRIVES
E321 19        DAD      D
E322 C9        RET

```

```

E323 3E00      BUILD  MVI      A,0
E324 =        HEAD   EQU    $-1
E325 17        RAL
E326 17        RAL
E327 17        RAL
E328 17        RAL
E329 F600      ORI      0
E32A =        HDDISK EQU    $-1
E32B EEF0      XRI      0FFH
E32D C9        RET

```

```

E32E =        DRIVES EQU    $
                        REPT  MAXHD
                        DB     0FFH
                        ENDM
E32E+FF      DB     0FFH
                        ENDIF

```

```

*****
*
* XLT TABLES (SECTOR SKEW TABLES) FOR CP/M 2.0. THESE TABLES
* DEFINE THE SECTOR TRANSLATION THAT OCCURS WHEN MAPPING CP/M
* SECTORS TO PHYSICAL SECTORS ON THE DISK. THERE IS ONE SKEW
* TABLE FOR EACH OF THE POSSIBLE SECTOR SIZES. CURRENTLY THE
* TABLES ARE LOCATED ON TRACK 0 SECTORS 6 AND 8. THEY ARE
* LOADED INTO MEMORY IN THE CBIOS RAM BY THE COLD BOOT ROUTINE.
*

```

*

| | | | | |
|------|------------|--------|----|-------------------------|
| E32F | 00 | XLT128 | IF | MAXFLOP NE 0 |
| E330 | 01070D1319 | | DB | 0 |
| E335 | 050B1117 | | DB | 1,7,13,19,25 |
| E339 | 03090F15 | | DB | 5,11,17,23 |
| E33D | 02080E141A | | DB | 3,9,15,21 |
| E342 | 060C1218 | | DB | 2,8,14,20,26 |
| E346 | 040A1016 | | DB | 6,12,18,24 |
| | | | | 4,10,16,22 |
| E34A | 00 | XLT256 | DB | 0 |
| E34B | 0102131425 | | DB | 1,2,19,20,37,38 |
| E351 | 0304151627 | | DB | 3,4,21,22,39,40 |
| E357 | 0506171829 | | DB | 5,6,23,24,41,42 |
| E35D | 0708191A2B | | DB | 7,8,25,26,43,44 |
| E363 | 090A1B1C2D | | DB | 9,10,27,28,45,46 |
| E369 | 0B0C1D1E2F | | DB | 11,12,29,30,47,48 |
| E36F | 0D0E1F2031 | | DB | 13,14,31,32,49,50 |
| E375 | 0F10212233 | | DB | 15,16,33,34,51,52 |
| E37B | 11122324 | | DB | 17,18,35,36 |
| E37F | 00 | XLT512 | DB | 0 |
| E380 | 0102030411 | | DB | 1,2,3,4,17,18,19,20 |
| E388 | 2122232431 | | DB | 33,34,35,36,49,50,51,52 |
| E390 | 0506070815 | | DB | 5,6,7,8,21,22,23,24 |
| E398 | 2526272835 | | DB | 37,38,39,40,53,54,55,56 |
| E3A0 | 090A0B0C19 | | DB | 9,10,11,12,25,26,27,28 |
| E3A8 | 292A2B2C39 | | DB | 41,42,43,44,57,58,59,60 |
| E3B0 | 0D0E0F101D | | DB | 13,14,15,16,29,30,31,32 |
| E3B8 | 2D2E2F30 | | DB | 45,46,47,48 |
| E3BC | 00 | XLT124 | DB | 0 |
| E3BD | 0102030405 | | DB | 1,2,3,4,5,6,7,8 |
| E3C5 | 191A1B1C1D | | DB | 25,26,27,28,29,30,31,32 |
| E3CD | 3132333435 | | DB | 49,50,51,52,53,54,55,56 |
| E3D5 | 090A0B0C0D | | DB | 9,10,11,12,13,14,15,16 |
| E3DD | 2122232425 | | DB | 33,34,35,36,37,38,39,40 |
| E3E5 | 393A3B3C3D | | DB | 57,58,59,60,61,62,63,64 |
| E3ED | 1112131415 | | DB | 17,18,19,20,21,22,23,24 |
| E3F5 | 292A2B2C2D | | DB | 41,42,43,44,45,46,47,48 |

*
* EACH OF THE FOLLOWING TABLES DESCRIBES A DISKETTE WITH THE *
* SPECIFIED CHARACTERISTICS. *
*

*
* THE FOLLOWING DPB DEFINES A DISKETTE FOR 128 BYTE SECTORS, *
* SINGLE DENSITY, AND SINGLE SIDED. *
*

```

E3FD 1A00    DPB128S DW      26      ;CP/M SECTORS/TRACK
E3FF 03      DB        3      ;BSH
E400 07      DB        7      ;BLM
E401 00      DB        0      ;EXM
E402 F200    DW      242     ;DSM
E404 3F00    DW        63     ;DRM
E406 C0      DB      0C0H    ;AL0
E407 00      DB        0      ;AL1
E408 1000    DW       16     ;CKS
E40A 0200    DW         2     ;OFF
E40C 01      DB       1H     ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                                ;8 IF DOUBLE SIDED.
    
```

*
* THE FOLLOWING DPB DEFINES A DISKETTE FOR 256 BYTE SECTORS,
* DOUBLE DENSITY, AND SINGLE SIDED.
*

```

E40D 3400    DPB256S DW      52      ;CP/M SECTORS/TRACK
E40F 04      DB         4     ;BSH
E410 0F      DB       15     ;BLM
E411 00      DB         0     ;EXM
E412 F200    DW      242     ;DSM
E414 7F00    DW      127     ;DRM
E416 C0      DB      0C0H    ;AL0
E417 00      DB         0     ;AL1
E418 2000    DW       32     ;CKS
E41A 0200    DW         2     ;OFF
E41C 12      DB      12H     ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                                ;8 IF DOUBLE SIDED.
    
```

*
* THE FOLLOWING DPB DEFINES A DISKETTE AS 512 BYTE SECTORS,
* DOUBLE DENSITY, AND SINGLE SIDED.
*

```

E41D 3C00    DPB512S DW      60      ;CP/M SECTORS/TRACK
E41F 04      DB         4     ;BSH
E420 0F      DB       15     ;BLM
E421 00      DB         0     ;EXM
E422 1801    DW     280     ;DSM
E424 7F00    DW      127     ;DRM
E426 C0      DB      0C0H    ;AL0
E427 00      DB         0     ;AL1
E428 2000    DW       32     ;CKS
E42A 0200    DW         2     ;OFF
E42C 33      DB     33H     ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                                ;LOG2(#BYTES PER SECTOR/128) + 1 +
    
```

;8 IF DOUBLE SIDED.

```
*****
*
* THE FOLLOWING DPB DEFINES A DISKETTE AS 1024 BYTE SECTORS,
* DOUBLE DENSITY, AND SINGLE SIDED.
*
```

```
E42D 4000 DP1024S DW 64 ;CP/M SECTORS/TRACK
E42F 04 DB 4 ;BSH
E430 0F DB 15 ;BLM
E431 00 DB 0 ;EXM
E432 2B01 DW 299 ;DSM
E434 7F00 DW 127 ;DRM
E436 C0 DB 0C0H ;AL0
E437 00 DB 0 ;AL1
E438 2000 DW 32 ;CKS
E43A 0200 DW 2 ;OFF
E43C 74 DB 74H ;16*(#CPM SECTORS/PHYSICAL SECTOR) -1) +
;LOG2(#BYTES PER SECTOR/128) + 1 +
;8 IF DOUBLE SIDED.
```

```
*****
*
* THE FOLLOWING DPB DEFINES A DISKETTE FOR 128 BYTE SECTORS,
* SINGLE DENSITY, AND DOUBLE SIDED.
*
```

```
E43D 3400 DPB128D DW 52 ;CP/M SECTORS/TRACK
E43F 04 DB 4 ;BSH
E440 0F DB 15 ;BLM
E441 01 DB 1 ;EXM
E442 F200 DW 242 ;DSM
E444 7F00 DW 127 ;DRM
E446 C0 DB 0C0H ;AL0
E447 00 DB 0 ;AL1
E448 2000 DW 32 ;CKS
E44A 0200 DW 2 ;OFF
E44C 09 DB 9H
```

```
*****
*
* THE FOLLOWING DPB DEFINES A DISKETTE AS 256 BYTE SECTORS,
* DOUBLE DENSITY, AND DOUBLE SIDED.
*
```

```
E44D 6800 DPB256D DW 104 ;CP/M SECTORS/TRACK
E44F 04 DB 4 ;BSH
E450 0F DB 15 ;BLM
E451 00 DB 0 ;EXM
E452 E601 DW 486 ;DSM
E454 FF00 DW 255 ;DRM
E456 F0 DB 0F0H ;AL0
```

E457 00 DB 0 ;AL1
E458 4000 DW 64 ;CKS
E45A 0200 DW 2 ;OFF
E45C 1A DB 1AH

*
* THE FOLLOWING DPB DEFINES A DISKETTE AS 512 BYTE SECTORS,
* DOUBLE DENSITY, AND DOUBLE SIDED.
*

E45D 7800 DPB512D DW 120 ;CP/M SECTORS/TRACK
E45F 04 DB 4 ;BSH
E460 0F DB 15 ;BLM
E461 00 DB 0 ;EXM
E462 3102 DW 561 ;DSM
E464 FF00 DW 255 ;DRM
E466 F0 DB 0F0H ;AL0
E467 00 DB 0 ;AL1
E468 4000 DW 64 ;CKS
E46A 0200 DW 2 ;OFF
E46C 3B DB 3BH

*
* THE FOLLOWING DPB DEFINES A DISKETTE AS 1024 BYTE SECTORS,
* DOUBLE DENSITY, AND DOUBLE SIDED.
*

E46D 8000 DP1024D DW 128 ;CP/M SECTORS/TRACK
E46F 04 DB 4 ;BSH
E470 0F DB 15 ;BLM
E471 00 DB 0 ;EXM
E472 5702 DW 599 ;DSM
E474 FF00 DW 255 ;DRM
E476 F0 DB 0F0H ;AL0
E477 00 DB 0 ;AL1
E478 4000 DW 64 ;CKS
E47A 0200 DW 2 ;OFF
E47C 7C DB 7CH
ENDIF

*
* THE FOLLOWING DPB DEFINES A 10 MEGABYTE HARD DISK, WITH 512
* BYTE SECTORS.
*

IF MAXHD NE 0
IF M26 NE 0
E47D 0004 DPBHD1 DW 1024 ;CP/M SECTORS/TRACK
E47F 05 DB 5 ;BSH
E480 1F DB 31 ;BLM

```

E481 01          DB          1          ;EXM
E482 B507        DW          1973        ;DSM
E484 FF01        DW          511         ;DRM
E486 FF          DB          0FFH       ;AL0
E487 FF          DB          0FFH       ;AL1
E488 0000        DW          0          ;CKS
E48A 0100        DW          1          ;OFF
E48C 33          DB          33H        ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
;LOG2(#BYTES PER SECTOR/128) + 1 +
;8 IF DOUBLE SIDED.

E48D 0004        DPBHD2 DW          1024        ;CP/M SECTORS/TRACK
E48F 05          DB          5          ;BSH
E490 1F          DB          31         ;BLM
E491 01          DB          1          ;EXM
E492 B507        DW          1973        ;DSM
E494 FF01        DW          511         ;DRM
E496 FF          DB          0FFH       ;AL0
E497 FF          DB          0FFH       ;AL1
E498 0000        DW          0          ;CKS
E49A 4000        DW          64         ;OFF
E49C 33          DB          33H        ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
;LOG2(#BYTES PER SECTOR/128) + 1 +
;8 IF DOUBLE SIDED.

E49D 0004        DPBHD3 DW          1024        ;CP/M SECTORS/TRACK
E49F 05          DB          5          ;BSH
E4A0 1F          DB          31         ;BLM
E4A1 01          DB          1          ;EXM
E4A2 B507        DW          1973        ;DSM
E4A4 FF01        DW          511         ;DRM
E4A6 FF          DB          0FFH       ;AL0
E4A7 FF          DB          0FFH       ;AL1
E4A8 0000        DW          0          ;CKS
E4AA 7F00        DW          127        ;OFF
E4AC 33          DB          33H        ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
;LOG2(#BYTES PER SECTOR/128) + 1 +
;8 IF DOUBLE SIDED.

                ENDIF
                IF          M10 NE 0
DPBHD1          DW          336         ;CP/M SECTORS/TRACK
                DB          5          ;BSH
                DB          31         ;BLM
                DB          1          ;EXM
                DW          1269        ;DSM
                DW          511         ;DRM
                DB          0FFH       ;AL0
                DB          0FFH       ;AL1
                DW          0          ;CKS
                DW          1          ;OFF
                DB          33H        ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
;LOG2(#BYTES PER SECTOR/128) + 1 +
;8 IF DOUBLE SIDED.

DPBHD2          DW          336         ;CP/M SECTORS/TRACK
                DB          5          ;BSH
                DB          31         ;BLM
                DB          1          ;EXM

```

```

DW      1280      ;DSM
DW      511       ;DRM
DB      0FFH     ;AL0
DB      0FFH     ;AL1
DW      0        ;CKS
DW      122      ;OFF
DB      33H      ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                ;8 IF DOUBLE SIDED.

```

ENDIF

```

IF      M20 NE 0
DPBHD1 DW      672      ;CP/M SECTORS/TRACK
DB      5            ;BSH
DB      31          ;BLM
DB      1           ;EXM
DW      2015       ;DSM
DW      511       ;DRM
DB      0FFH     ;AL0
DB      0FFH     ;AL1
DW      0        ;CKS
DW      1        ;OFF
DB      33H      ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                ;8 IF DOUBLE SIDED.

```

```

DPBHD2 DW      672      ;CP/M SECTORS/TRACK
DB      5            ;BSH
DB      31          ;BLM
DB      1           ;EXM
DW      2015       ;DSM
DW      511       ;DRM
DB      0FFH     ;AL0
DB      0FFH     ;AL1
DW      0        ;CKS
DW      98        ;OFF
DB      33H      ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                ;8 IF DOUBLE SIDED.

```

```

DPBHD3 DW      672      ;CP/M SECTORS/TRACK
DB      5            ;BSH
DB      31          ;BLM
DB      1           ;EXM
DW      1028      ;DSM
DW      511       ;DRM
DB      0FFH     ;AL0
DB      0FFH     ;AL1
DW      0        ;CKS
DW      195      ;OFF
DB      33H      ;16*((#CPM SECTORS/PHYSICAL SECTOR) -1) +
                ;LOG2(#BYTES PER SECTOR/128) + 1 +
                ;8 IF DOUBLE SIDED.

```

ENDIF
ENDIF

*

* CP/M DISK PARAMETER HEADERS, UNINITIALIZED. *
 * * * * *

```

HEADER  MACRO  ND,DPB
          DW      0           ;TRANSLATION TABLE FILLED IN LATER
          DW      0,0,0       ;SCRATCH
          DW      DIRBUF     ;DIRECTORY BUFFER
          DW      DPB        ;DPB FILLED IN LATER
          DW      CSV&ND     ;DIRECTORY CHECK VECTOR
          DW      ALV&ND     ;ALLOCATION VECTOR
          ENDM
    
```

```

E4AD =    DPBASE EQU      $
0000 #    DN      SET      0
          IF      FIRST
          REPT    MAXHD     ;GENERATE HARD DISK DPH'S FOLLOWED
          HEADER  %DN,DPBHD1 ; BY FLOPPY DPH'S
          DN      SET      DN+1
          HEADER  %DN,DPBHD2
          DN      SET      DN+1
          IF      (M26 NE 0) OR (M20 NE 0)
          HEADER  %DN,DPBHD3
          DN      SET      DN+1
          ENDIF
          ENDM
    
```

```

          REPT    MAXFLOP
          DN      HEADER  %DN,0
          SET      DN+1
          ENDM
          ELSE
          REPT    MAXFLOP     ;GENERATE FLOPPY DPH'S FOLLOWED BY
          DN      HEADER  %DN,0 ; HARD DISK DPH'S
          SET      DN+1
          ENDM
    
```

```

E4AD+0000    DW      0           ;TRANSLATION TABLE FILLED IN LATER
E4AF+0000000000    DW      0,0,0       ;SCRATCH
E4B5+07E9    DW      DIRBUF     ;DIRECTORY BUFFER
E4B7+0000    DW      0           ;DPB FILLED IN LATER
E4B9+D2E9    DW      CSV0       ;DIRECTORY CHECK VECTOR
E4BB+87E9    DW      ALV0       ;ALLOCATION VECTOR
E4BD+0000    DW      0           ;TRANSLATION TABLE FILLED IN LATER
E4BF+0000000000    DW      0,0,0       ;SCRATCH
E4C5+07E9    DW      DIRBUF     ;DIRECTORY BUFFER
E4C7+0000    DW      0           ;DPB FILLED IN LATER
E4C9+5DEA    DW      CSV1       ;DIRECTORY CHECK VECTOR
E4CB+12EA    DW      ALV1       ;ALLOCATION VECTOR
    
```

```

          REPT    MAXHD
          DN      HEADER  %DN,DPBHD1
          SET      DN+1
          DN      HEADER  %DN,DPBHD2
          SET      DN+1
          IF      (M26 NE 0) OR (M20 NE 0)
          DN      HEADER  %DN,DPBHD3
          SET      DN+1
          ENDIF
    
```



```

ENDM
E4CD+0000 DW 0 ;TRANSLATION TABLE FILLED IN LATER
E4CF+0000000000 DW 0,0,0 ;SCRATCH
E4D5+07E9 DW DIRBUF ;DIRECTORY BUFFER
E4D7+7DE4 DW DPBHD1 ;DPB FILLED IN LATER
E4D9+94EB DW CSV2 ;DIRECTORY CHECK VECTOR
E4DB+9DEA DW ALV2 ;ALLOCATION VECTOR
E4DD+0000 DW 0 ;TRANSLATION TABLE FILLED IN LATER
E4DF+0000000000 DW 0,0,0 ;SCRATCH
E4E5+07E9 DW DIRBUF ;DIRECTORY BUFFER
E4E7+8DE4 DW DPBHD2 ;DPB FILLED IN LATER
E4E9+8BEC DW CSV3 ;DIRECTORY CHECK VECTOR
E4EB+94EB DW ALV3 ;ALLOCATION VECTOR
E4ED+0000 DW 0 ;TRANSLATION TABLE FILLED IN LATER
E4EF+0000000000 DW 0,0,0 ;SCRATCH
E4F5+07E9 DW DIRBUF ;DIRECTORY BUFFER
E4F7+9DE4 DW DPBHD3 ;DPB FILLED IN LATER
E4F9+82ED DW CSV4 ;DIRECTORY CHECK VECTOR
E4FB+8BEC DW ALV4 ;ALLOCATION VECTOR
ENDIF

```

```

*****
*
* CBIOS RAM LOCATIONS THAT DON'T NEED INITIALIZATION.
*
*****

```

```

E4FD 0000 CPMSEC DW 0 ;CP/M SECTOR #
E4FF 00 CPMDRV DB 0 ;CP/M DRIVE #
E500 00 CPMTRK DB 0 ;CP/M TRACK #
E501 0000 TRUESEC DW 0 ;DISK JOCKEY SECTOR THAT CONTAINS CP/M SECTOR
E503 00 BUFDRV DB 0 ;DRIVE THAT BUFFER BELONGS TO
E504 00 BUFTRK DB 0 ;TRACK THAT BUFFER BELONGS TO
E505 0000 BUFSEC DW 0 ;SECTOR THAT BUFFER BELONGS TO
E507 = BUFFER EQU $

```

```

*****
*
* SIGNON MESSAGE OUTPUT DURING COLD BOOT.
*
*****

```

```

HEXNUM MACRO NUM
IF (NUM/16) > 9
DB (NUM/16 AND 0FH) + 'A' - 10
ELSE
DB (NUM/16 AND 0FH) + '0'
ENDIF
IF (NUM AND 0FH) > 9
DB (NUM AND 0FH) + 'A' - 10
ELSE
DB (NUM AND 0FH) + '0'
ENDIF
ENDM

```

```

E507 0D0A0A PROMPT DB ACR,ALF,ALF

```

```

E50A 4D6F72726F      DB      'Morrow Designs '
E519 36              DB      '0'+MSIZE/10      ;CP/M MEMORY SIZE
E51A 30              DB      '0'+(MSIZE MOD 10)
E51B 4B2043502F      DB      'K CP/M '        ;CP/M VERSION NUMBER
E522 32              DB      CPMREV/10+'0'
E523 2E              DB      '.'
E524 32              DB      (CPMREV MOD 10)+'0'
E525 2C20436269      DB      ', Cbios rev '
E531 322E           DB      REVNUM/10+'0', '.' ;CBIOS REVISION NUMBER
E533 38              DB      REVNUM MOD 10+'0'
E534 2E              IF      MAXHD NE 0
E535 32              DB      '.'
E536 36              DB      MREV/10+'0'
E537 0D0A           DB      MREV MOD 10+'0'
E539 466F7220       IF      (M10 OR M20) AND SDELAY
E540 32              DB      'M'
E541 32              ENDIF
E542 32              IF      (M10 OR M20) AND NOT SDELAY
E543 32              DB      'F'
E544 32              ENDIF
E545 32              ENDIF
E546 32              DB      ACR, ALF
E547 32              DB      'For '
E548 32              IF      MAXFLOP NE 0
E549 32              DB      'a Disk Jockey 2D @ '
E550+46             HEXNUM  %(ORIGIN/256)
E551+30             DB      (240/16 AND 0FH) + 'A' - 10
E552 30304820       DB      (240 AND 0FH) + '0'
E553 30304820       DB      '00H '
E554 30304820       ENDIF
E555 30304820       IF      (MAXHD NE 0) AND (MAXFLOP NE 0)
E556 616E6420       DB      'and '
E557 616E6420       ENDIF
E558 616E6420       IF      MAXHD NE 0
E559 616E6420       IF      MAXHD EQ 1
E560 616E6420       DB      'an '
E561 616E6420       ENDIF
E562 616E6420       IF      MAXHD EQ 2
E563 616E6420       DB      'two '
E564 616E6420       ENDIF
E565 616E6420       IF      MAXHD EQ 3
E566 616E6420       DB      'three '
E567 616E6420       ENDIF
E568 616E6420       IF      MAXHD EQ 4
E569 616E6420       DB      'four '
E570 616E6420       ENDIF
E571 616E6420       IF      MREV EQ 10
E572 616E6420       DB      'M10 '
E573 616E6420       ENDIF
E574 616E6420       IF      MREV EQ 20
E575 616E6420       DB      'M20 '
E576 616E6420       ENDIF
E577 616E6420       IF      MREV EQ 26

```

```

E55D 4D323620 DB 'M26 '
                ENDIF
E561 6861726420 DB 'hard disk'
                IF MAXHD NE 1
                DB 's'
                ENDIF
E56A 204020 DB ' @ '
                HEXNUM %HDORG
E56D+35 DB (80/16 AND 0FH) + '0'
E56E+30 DB (80 AND 0FH) + '0'
E56F 482E DB 'H.'
                ENDIF
E571 0D0A DB ACR,ALF
E573 0D0A DB ACR,ALF
E575 2020202020 DB ' THE W6GO/K6HHD LIST'
E58F 0D0A DB ACR,ALF
E591 2020202020 DB ' Electronics Enterprises'
E5AD 0D0A DB ACR,ALF
E5AF 2020202020 DB ' Rio Linda, California'
E5CA 0D0A DB ACR,ALF
E5CC 00 DB 0
    
```

```

*****
*
* UTILITY ROUTINE TO OUTPUT THE MESSAGE POINTED AT BY H&L,
* TERMINATED WITH A NULL.
*
*****
    
```

```

E5CD 7E MESSAGE MOV A,M ;GET A CHARACTER OF THE MESSAGE
E5CE 23 INX H ;BUMP TEXT POINTER
E5CF A7 ANA A ;TEST FOR END
E5D0 C8 RZ ;RETURN IF DONE
E5D1 E5 PUSH H ;SAVE POINTER TO TEXT
E5D2 4F MOV C,A ;OUTPUT CHARACTER IN C
E5D3 CD0CDD CALL COUT ;OUTPUT THE CHARACTER
E5D6 E1 POP H ;RESTORE THE POINTER
E5D7 C3CDE5 JMP MESSAGE ;CONTINUE UNTIL NULL REACHED
    
```

```

*****
*
* CBOOT IS THE COLD BOOT LOADER. ALL OF CP/M HAS BEEN LOADED IN
* WHEN CONTROL IS PASSED HERE.
*
*****
    
```

```

E5DA 310001 CBOOT LXI SP,TPA ;SET UP STACK

E5DD 3EC0 MVI A,INTIOBY
E5DF 320300 STA IOBYTE
E5E2 CD2DDE CALL TINIT ;INITIALIZE THE TERMINAL

E5E5 2107E5 LXI H,PROMPT ;PREP FOR SENDING SIGNON MESSAGE
E5E8 CDCDE5 CALL MESSAGE ;SEND THE PROMPT
E5EB AF XRA A ;SELECT DISK A
E5EC 32FFE4 STA CPMDRV
    
```

```

CP/M MACRO ASSEM 2.0      #044      *** Cbios For CP/M Ver. 2.2 ***

E5EF 320400              STA      CDISK

                          IF      (MAXFLOP NE 0) AND FIRST
                          STA      FLOPFLG
                          ENDIF

E5F2 2103DD              LXI      H, BIOS+3
E5F5 2201DD              SHLD    BIOS+1
E5F8 C358DE              JMP      GOCPM

E5FB                      DS      512-($-BUFFER) ;MAXIMUM SIZE BUFFER FOR 512 BYTE SECTORS

E707                      IF      MAXFLOP NE 0
                          DS      512          ;ADDITIONAL SPACE FOR FLOPPIES 1K SECTORS
                          ENDIF

E907                      IF      (MAXFLOP NE 0) OR (MAXHD NE 0)
DIRBUF                    DS      128          ;DIRECTORY BUFFER
                          ENDIF

                          ALLOC    MACRO    ND, AL, CS
                          ALV&ND  DS      AL
                          CSV&ND  DS      CS
                          ENDM

0000 #                    DN      SET      0

                          IF      NOT FIRST
                          REPT    MAXFLOP
                          ALLOC    %DN, 75, 64
                          DN      SET      DN+1
                          ENDM

E987+                    ALV0     DS      75
E9D2+                    CSV0     DS      64
EA12+                    ALV1     DS      75
EA5D+                    CSV1     DS      64

                          REPT    MAXHD
                          IF      M26 NE 0
                          ALLOC    %DN, 247, 0
                          DN      SET      DN+1
                          ALLOC    %DN, 247, 0
                          DN      SET      DN+1
                          ALLOC    %DN, 247, 0
                          DN      SET      DN+1
                          ENDIF
                          IF      M10 NE 0
                          ALLOC    %DN, 159, 0
                          DN      SET      DN+1
                          ALLOC    %DN, 161, 0
                          DN      SET      DN+1
                          ENDIF
                          IF      M20 NE 0
                          ALLOC    %DN, 252, 0
                          DN      SET      DN+1
                          ALLOC    %DN, 252, 0
                          DN      SET      DN+1
                          ALLOC    %DN, 129, 0

```

```

        DN      SET      DN+1
                ENDIF
                ENDM
EA9D+    ALV2    DS      247
EB94+    CSV2    DS      0
EB94+    ALV3    DS      247
EC8B+    CSV3    DS      0
EC8B+    ALV4    DS      247
ED82+    CSV4    DS      0

                ELSE

                REPT     MAXHD
                IF      M26 NE 0
                ALLOC   %DN,247,0
                DN      SET      DN+1
                ALLOC   %DN,247,0
                DN      SET      DN+1
                ALLOC   %DN,247,0
                DN      SET      DN+1
                ENDIF
                IF      M10 NE 0
                ALLOC   %DN,159,0
                DN      SET      DN+1
                ALLOC   %DN,161,0
                DN      SET      DN+1
                ENDIF
                IF      M20 NE 0
                ALLOC   %DN,252,0
                DN      SET      DN+1
                ALLOC   %DN,252,0
                DN      SET      DN+1
                ALLOC   %DN,129,0
                DN      SET      DN+1
                ENDIF
                ENDM
                REPT     MAXFLOP
                ALLOC   %DN,75,64
                DN      SET      DN+1
                ENDM
                ENDIF
                END
ED82
```

| | | | | |
|--------------|--------------|---------------|--------------|--------------|
| 0006 AACK | E22F ACCOK | 000D ACR | 0003 AETX | 000A ALF |
| E987 ALV0 | EA12 ALV1 | EA9D ALV2 | EB94 ALV3 | EC8B ALV4 |
| DEAB AUTOFLG | CF00 BDOS | A000 BIAS | DD00 BIOS | E503 BUFDRV |
| 0080 BUFF | E507 BUFFER | E505 BUFSEC | E504 BUFTRK | E10D BUFWRN |
| E323 BUILD | E5DA CBOOT | C700 CCP | 0004 CDISK | DE08 CICRT |
| DE08 CIPTR | DD88 CITBLE | F003 CITTY | DDF3 CIUC1 | DE08 CIUR1 |
| DE08 CIUR2 | DEA3 CLDBOT | DE8E CLDCMND | 001A CLEAR | DE3B COCRT |
| DEAC COLDBEG | DEBA COLDEND | DDC9 COLPT | 0004 COMPLT | DD42 CONIN |
| DD48 CONIN1 | DD57 CONOUT | DD36 CONST | DDC9 COPTP | DE46 COPTR |
| DE4D COPTR1 | DD90 COTBLE | F006 COTTY | DDD4 COUL1 | DDF2 COUNT |
| DDC9 COUP1 | DDC9 COUP2 | DD0C COUT | E0ED CPMDMA | E4FF CPMDRV |
| 0016 CPMREV | E4FD CPMSEC | E500 CPMTRK | DE1C CSCRT | DE1C CSPTR |
| DD3C CSREADR | DDB8 CSRTBLE | DDB0 CSTBLE | DE14 CSTTY | DDFF CSUC1 |
| DE1C CSUR1 | DE1C CSUR2 | E9D2 CSV0 | EA5D CSV1 | EB94 CSV2 |
| EC8B CSV3 | ED82 CSV4 | DEAA CWFLG | 0008 DBLSID | E066 DCRC |
| E1E1 DECIDE | E1DD DECIDGO | E20F DELAY | E212 DELOOP | E907 DIRBUF |
| E0B9 DIVDONE | E068 DIVLOG | E06A DIVLOGX | E0AB DIVLOOP | F400 DJBOOT |
| F003 DJCIN | F006 DJCOUT | F42D DJDEN | F412 DJDMA | DD33 DJDRV |
| F42A DJERR | F409 DJHOME | F400 DJRAM | F415 DJREAD | F40F DJSEC |
| F41B DJSEL | F430 DJSIDE | F427 DJSTAT | F40C DJTRK | F021 DJTSTAT |
| F418 DJWRITE | DF4A DONOP | E46D DP1024D | E42D DP1024S | E43D DPB128D |
| E3FD DPB128S | E44D DPB256D | E40D DPB256S | E45D DPB512D | E41D DPB512S |
| E4AD DPBASE | E47D DPBHD1 | E48D DPBHD2 | E49D DPBHD3 | E32E DRIVES |
| E001 DRVHD | E318 DRVPTR | 0020 DRVRDY | 0007 DSKCLK | E0C8 DTSLOP |
| 0005 ENTRY | E19E FILL | 0000 FIRST | DFAA FLOPOK | E10C FLUSH |
| E1C6 FREAD | E071 GETDPB | E262 GETSPT | DE58 GOCPM | E27F HDADD |
| 0051 HDCMND | 0050 HDCNTL | 0053 HDDATA | E32A HDDISK | E242 HDDMA |
| E1E9 HDDRV | 0052 HDFUNC | E1FA HDHOME | 0050 HDORG | E2E3 HDPREP |
| E265 HDREAD | 0051 HDRESLT | 0004 HDRLEN | E250 HDSEC | E308 HDSECTR |
| E247 HDSIDE | 0020 HDSPT | 0050 HDSTAT | E21B HDTRK | E229 HDTRK2 |
| E29A HDWRITE | E324 HEAD | DF51 HOME | 0000 IDBUFF | 0040 INDEX |
| E034 INDX1 | E03B INDX2 | 00C0 INTIOBY | E0FA INTO | 0003 IOBYTE |
| 0008 ISBUFF | DD77 LIST | DD7A LIST1 | DD82 LISTST | 0003 LOGDSK |
| DE25 LSLPT | DDC0 LSTBLE | DD98 LTBLE | 0000 M10 | 0000 M20 |
| 0001 M26 | 0002 MAXFLOP | 0001 MAXHD | 00F7 MDIR | E5CD MESSAGE |
| E0D7 MOVE | E1D2 MOVER | E1D4 MOVLOP | 001A MREV | 003C MSIZE |
| DF1E NEWDMA | DEFF NEWSEC | E12D NOADJUST | DF16 NOWRAP | 00FB NSTEP |
| 00FC NULL | 4A00 OFFSETC | 0002 OPDONE | F000 ORIGIN | E0F5 OUTOF |
| DD72 PNCH1 | E119 PREP | E2C9 PROCESS | E507 PROMPT | 0004 PSTEP |
| DDA0 PTBLE | DD6C PUNCH | DDE9 PWAIT | E0F0 RDWR | DD62 READER |
| E099 READ | DD65 READERA | DD68 READR1 | DE2A READY | E09D REDWRT |
| 000A RETRIES | 0002 RETRY | E122 RETRYLP | E17F RETRYOP | 001C REVNUM |
| 0001 RSECT | DDA8 RTBLE | E285 RTLOOP | 0005 SCENBL | 0001 SDELAY |
| 0200 SECLN | E0DC SECPSEC | E09E SECSIZ | DF58 SECTRAN | DD4C SELDEV |
| DF4B SETDMA | DF93 SETDRV | E049 SETDRV1 | DF45 SETSEC | E210 SETTLE |
| DF53 SETTRK | DF6E SIDEA | DFEF SIDEOK | DF71 SIDEONE | DF77 SIDETWO |
| E233 SLOOP | DE17 STAT | E1FF STEPO | DDFF SUBFP | E01D TDELAY |
| DE2D TINIT | 0001 TKZERO | 0008 TMOUT | 0100 TPA | DF60 TRANFP |
| DF8F TRANHD | E501 TRUESEC | DEBB WARMBEG | DEBB WARMEND | DEFE WARMLOD |
| DF32 WARMRD | DD03 WBOOTE | DEBC WBOOT | 0000 WBOT | 000F WENABL |
| 0010 WFAULT | DEC0 WFLG | 000B WRESET | E092 WRITE | E104 WRITTPY |
| DF35 WRMREAD | E248 WSDONE | 0005 WSECT | E2A6 WTLOOP | E3BC XLT124 |
| E32F XLT128 | E34A XLT256 | E37F XLT512 | E08A XLTS | E307 ZKEY |
| E062 ZRET | | | | |