

-- Includes.Mesa Edited by Sandman on August 3, 1978 11:54 AM

DIRECTORY

```

AltoDefs: FROM "altodefs",
AltoFileDefs: FROM "altofiledefs",
BcdDefs: FROM "bcddefs",
ControlDefs: FROM "controldefs",
DirectoryDefs: FROM "directorydefs",
ImageDefs: FROM "imagedefs",
IODefs: FROM "iodefs",
MiscDefs: FROM "miscdefs",
Mopcodes: FROM "mopcodes",
OutputDefs: FROM "outputdefs",
SymDefs: FROM "SymDefs",
SegmentDefs: FROM "segmentdefs",
StringDefs: FROM "stringdefs",
StreamDefs: FROM "streamdefs",
SymbolTableDefs: FROM "SymbolTableDefs",
SystemDefs: FROM "SystemDefs",
TimeDefs: FROM "timedefs";

```

DEFINITIONS FROM AltoDefs, AltoFileDefs, SegmentDefs, OutputDefs;

Includes: PROGRAM

```

IMPORTS DirectoryDefs, IODefs, MiscDefs, OutputDefs, SegmentDefs,
StringDefs, SymbolTableDefs, SystemDefs, TimeDefs, StreamDefs = PUBLIC
BEGIN

```

```

NullTime: TimeDefs.PackedTime = [0,0];
NullStamp: BcdDefs.VersionStamp = [FALSE, 0, 0, [0,0]];
SP: CHARACTER = ' ;
FF: CHARACTER = 14C;

```

```

FileEntry: TYPE = RECORD [
  link: FEPtr,
  name: STRING,
  includes: POINTER TO IncludeItem,
  includedBy: POINTER TO IncludeItem,
  stamp: BcdDefs.VersionStamp,
  mark: BOOLEAN,
  busy: BOOLEAN,
  bad: BOOLEAN];
FEPtr: TYPE = POINTER TO FileEntry;

```

fileList: POINTER TO FileEntry ← NIL;

```

IncludeItem: TYPE = RECORD [
  link: POINTER TO IncludeItem,
  includedFile: FEPtr,
  stamp: BcdDefs.VersionStamp];

```

```

TimeLess: PROCEDURE [a,b: TimeDefs.PackedTime] RETURNS [BOOLEAN] =
BEGIN
RETURN[IF a.highbits = b.highbits THEN a.lowbits < b.lowbits
ELSE a.highbits < b.highbits]
END;

```

```

CompareString: PROCEDURE [a,b: STRING] RETURNS [{less,equal,greater}] =
BEGIN

```

```

CharAnd: PROCEDURE [CHARACTER,WORD] RETURNS [CHARACTER] =
MACHINE CODE BEGIN Mopcodes.zAND END;

```

```

l: CARDINAL = MIN[a.length,b.length];

```

```

i: CARDINAL;

```

```

ca, cb: CHARACTER;

```

```

FOR i IN [0..l) DO

```

```

  ca ← a[i];

```

```

  cb ← b[i];

```

```

  IF ca IN ['a..'z] THEN ca ← CharAnd[ca,137B];

```

```

  IF cb IN ['a..'z] THEN cb ← CharAnd[cb,137B];

```

```

  IF ca < cb THEN RETURN[less];

```

```

  IF ca > cb THEN RETURN[greater];

```

```

  ENDOLOOP;

```

```

RETURN[SELECT a.length FROM

```

```

  < b.length => less,

```

```

  b.length => equal,

```

```

  ENDCASE => greater]

```

```

END;

CopyString: PROCEDURE [s: STRING] RETURNS [copy: STRING] =
BEGIN
  copy ← SystemDefs.AllocateHeapString[s.length];
  StringDefs.AppendString[copy,s];
  RETURN
END;

CheckNameInList: PROCEDURE [name: STRING] =
BEGIN
  p: FEPtr;
  FOR p ← fileList, p.link UNTIL p = NIL DO
    SELECT CompareString[p.name,name] FROM
      equal => BEGIN p.name ← name; RETURN END;
    ENDCASE;
  ENDLOOP;
END;

GetFile: PROCEDURE [name: STRING] RETURNS [p: FEPtr] =
BEGIN
  last: FEPtr ← LOOPHOLE[@fileList]; -- assumes link field is word zero
  FOR p ← fileList, p.link UNTIL p = NIL DO
    SELECT CompareString[p.name,name] FROM
      less => last ← p;
      equal => RETURN;
      ENDCASE => EXIT;
  ENDLOOP;
  p ← SystemDefs.AllocateHeapNode[SIZE[FileEntry]];
  p.link ← last.link;
  last.link ← p;
  p.name ← name;
  p.stamp ← NullStamp;
  p.mark ← p.busy ← p.bad ← FALSE;
  p.includes ← p.includedBy ← NIL;
  RETURN
END;

NewIncludeItem: PROCEDURE [link: POINTER TO IncludeItem, fe: FEPtr, stamp: BcdDefs.VersionStamp]
RETURNS [POINTER TO IncludeItem] =
BEGIN
  p: POINTER TO IncludeItem;
  last: POINTER TO IncludeItem ← LOOPHOLE[@link]; -- assumes link field is word zero
  FOR p ← link, p.link UNTIL p = NIL DO
    SELECT CompareString[p.includedFile.name,fe.name] FROM
      less => last ← p;
      equal => RETURN[link];
      ENDCASE => EXIT;
  ENDLOOP;
  p ← SystemDefs.AllocateHeapNode[SIZE[IncludeItem]];
  p.link ← last.link;
  last.link ← p;
  p.includedFile ← fe;
  p.stamp ← stamp;
  RETURN[link]
END;

InvalidObjectFile: ERROR [file:FileHandle] = CODE;

LoadSymbols: PROCEDURE [file:FileHandle] RETURNS [symseg:FileSegmentHandle] =
BEGIN
  bcd: POINTER TO BcdDefs.BCD;
  pages: AltoDefs.PageCount;
  mtb: CARDINAL;
  mti: BcdDefs.MTIndex = FIRST[BcdDefs.MTIndex];
  bcdseg: FileSegmentHandle ← NewFileSegment[file,1,1,Read];
  Cleanup: PROCEDURE =
  BEGIN
    Unlock[bcdseg];
    DeleteFileSegment[bcdseg];
    RETURN
  END;
  SwapIn[bcdseg];
  bcd ← FileSegmentAddress[bcdseg];
  IF (pages ← bcd.nPages) # 1 THEN

```

```

BEGIN
  Unlock[bcdseg];
  MoveFileSegment[bcdseg, 1, pages];
  SwapIn[bcdseg];
  bcd ← FileSegmentAddress[bcdseg];
  END;
IF bcd.versionident # BcdDefs.VersionID OR bcd.nModules # 1 THEN
  ERROR InvalidObjectFile[file ! UNWIND => Cleanup[]];
mtb ← LOOPHOLE[bcd,CARDINAL]+bcd.mtOffset;
symseg ← FindSegment[bcdseg, (mtb+mti).sseg, FALSE ! UNWIND => Cleanup[]];
IF symseg = NIL THEN ERROR InvalidObjectFile[file ! UNWIND => Cleanup[]];
Cleanup[];
RETURN
END;

FindSegment: PROCEDURE [seg: FileSegmentHandle, sgi: BcdDefs.SGIndex, long: BOOLEAN]
  RETURNS [FileSegmentHandle] =
  BEGIN
  ss: StringDefs.SubStringDescriptor;
  file: SegmentDefs.FileHandle;
  name: STRING ← [40];
  bcd: POINTER TO BcdDefs.BCD ← FileSegmentAddress[seg];
  sgh: BcdDefs.SGHandle ← LOOPHOLE[bcd+bcd.sgOffset, CARDINAL]+sgi;
  ssb: BcdDefs.NameString ← LOOPHOLE[bcd+bcd.ssOffset];
  IF sgh.file = BcdDefs.FTNull THEN RETURN[NIL]
  ELSE IF sgh.file = BcdDefs.FTself THEN file ← seg.file
  ELSE
  BEGIN
  f: BcdDefs.FTHandle =
    LOOPHOLE[bcd+bcd.ftOffset, CARDINAL]+sgh.file;
  ss ← [@ssb.string, f.name, ssb.size[f.name]];
  StringDefs.AppendSubString[name, @ss];
  CheckForExtension[name, ".bcd"];
  file ← NewFile[name, DefaultAccess, DefaultVersion];
  END;
  RETURN[NewFileSegment[file, sgh.base,
    sgh.pages + (IF long THEN sgh.extraPages ELSE 0), Read]];
  END;

CheckForExtension: PROCEDURE [name, ext: STRING] =
  BEGIN
  i: CARDINAL;
  FOR i IN [0..name.length) DO
    IF name[i] = '.' THEN RETURN;
  ENDLOOP;
  StringDefs.AppendString[name, ext];
  RETURN
  END;

ProcessIncludes: PROCEDURE [includer: FEPtr, symseg: FileSegmentHandle] =
  BEGIN OPEN SymbolTableDefs;
  symbols: SymbolTableBase = AcquireSymbolTable[TableForSegment[symseg]];
  mdLimit: SymDefs.MDIndex = LOOPHOLE[symbols.stHandle.mdBlock.size];
  mdi: SymDefs.MDIndex;
  includee: FEPtr;
  ss: StringDefs.SubStringDescriptor;
  sname: STRING ← [40];
  tname: STRING;
  i: CARDINAL;
  IODefs.WriteLine[includer.name];
  includer.stamp ← symbols.stHandle.version;
  FOR mdi ← FIRST[SymDefs.MDIndex] + SIZE[SymDefs.MDRecord], mdi + SIZE[SymDefs.MDRecord]
  UNTIL mdi = mdLimit DO
  symbols.SubStringForHash[@ss, (symbols.mdb+mdi).mdhti];
  sname.length ← 0;
  FOR i IN [0..ss.length) DO
    IF ss.base[ss.offset+i] = '.' THEN EXIT;
    StringDefs.AppendChar[sname, ss.base[ss.offset+i]];
  ENDLOOP;
  tname ← CopyString[sname];
  includee ← GetFile[tname];
  includer.includes ← NewIncludeItem[
    includer.includes, includee, (symbols.mdb+mdi).mdStamp];
  includee.includedBy ←
    NewIncludeItem[includee.includedBy, includer, NullStamp];
  ENDLOOP;

```

```

ReleaseSymbolTable[symbols];
RETURN
END;

StripExtension: PROCEDURE [name,ext:STRING] =
BEGIN OPEN StringDefs;
i, j: INTEGER;
ext.length ← 0;
i ← (j ← name.length) - 1;
IF name[i]='.' THEN i ← (j ← i) - 1;
UNTIL name[i] = '.' DO
  IF name[i] = '|' THEN j ← i;
  IF (i ← i-1) < 0 THEN RETURN;
ENDLOOP;
i ← i+1;
UNTIL i=j DO
  AppendChar[ext,name[i]];
  i ← i+1;
ENDLOOP;
RETURN
END;

ext: STRING ← [FilenameChars+1];

IsBCD: PROCEDURE [fp:POINTER TO FP, name:STRING]
RETURNS [BOOLEAN] =
BEGIN OPEN StringDefs;
okay: BOOLEAN ← TRUE;
tname: STRING;
IF names = NIL THEN
  BEGIN
  StripExtension[name,ext];
  okay ← EquivalentString[ext,"bcd"];
  IF okay THEN tname ← CopyString[name];
  END
ELSE [okay, tname] ← FindNameInList[name];
IF okay THEN AddFile[InsertFile[fp,Read], tname];
RETURN[FALSE]
END;

AddFile: PROCEDURE [file: FileHandle, name:STRING] =
BEGIN OPEN StringDefs;
syms: FileSegmentHandle;
fe: FEPtr;
i: CARDINAL;
BEGIN
  syms ← LoadSymbols[file
  ! InvalidObjectFile => GOTO invalidfile; ANY => GOTO badfile];
  FOR i IN [0..name.length) DO
    IF name[i] = '.' THEN
      BEGIN name.length ← i; EXIT END;
    ENDLOOP;
  fe ← GetFile[name];
  CheckNameInList[name];
  ProcessIncludes[fe, syms];
  DeleteFileSegment[syms];
  EXITS
  invalidfile => NULL;
  badfile =>
    BEGIN OPEN IODefs;
    WriteString["File "];
    WriteString[name];
    WriteLine[" is a bad file!!"];
    END;
  END;
END;

NameList: TYPE = POINTER TO NameItem;

NameItem: TYPE = RECORD [
  link: NameList,
  name: STRING];

names: NameList ← NIL;

```

```

AddName: PROCEDURE [name: STRING] =
  BEGIN
    n1: NameList ← SystemDefs.AllocateHeapNode[SIZE[NameItem]];
    n1↑ ← NameItem[link: names, name: CopyAndCheck[name]];
    names ← n1;
    RETURN
  END;

CopyAndCheck: PROCEDURE [name: STRING] RETURNS [s: STRING] =
  BEGIN
    i: CARDINAL;
    state: {none, ext, dot} ← none;
    FOR i IN [0..name.length) DO
      IF name[i] = '.' THEN BEGIN state ← ext; EXIT END;
    ENDOLOOP;
    IF name[name.length-1] = '.' THEN state ← dot;
    s ← SystemDefs.AllocateHeapString[name.length +
      CARDINAL[(SELECT state FROM dot => 0, ext => 1, ENDCASE => 5)]];
    StringDefs.AppendString[s, name];
    SELECT state FROM
      ext => StringDefs.AppendChar[s, '.];
      none => StringDefs.AppendString[s, ".bcd."L];
    ENDCASE;
    RETURN
  END;

FindNameInList: PROCEDURE [name: STRING] RETURNS [BOOLEAN, STRING] =
  BEGIN
    n1: NameList;
    FOR n1 ← names, n1.link UNTIL n1 = NIL DO
      IF StringDefs.EquivalentString[n1.name, name] THEN
        RETURN[TRUE, n1.name];
      ENDOLOOP;
    RETURN[FALSE, NIL];
  END;

PutStamp: PROCEDURE [s: BcdDefs.VersionStamp] =
  BEGIN
    PutTime[s.time];
    PutString[" #"];
    PutNumber[s.net, [8, FALSE, FALSE, 1]];
    PutString[" #"];
    PutNumber[s.host, [8, FALSE, FALSE, 1]];
    IF s.zapped THEN PutString[" zapped!!!"];
    RETURN
  END;

printDate: BOOLEAN;

FileName: PROCEDURE [fe: FEPtr] =
  BEGIN
    PutString[fe.name];
    IF ~printDate OR fe.stamp.time = NullTime THEN RETURN;
    PutString[" ("];
    PutStamp[fe.stamp];
    PutChar[']];
    RETURN
  END;

OutputStats: PROCEDURE =
  BEGIN
    badfile: BOOLEAN;
    fe: FEPtr;
    i: POINTER TO IncludeItem;
    printDate ← TRUE;
    FOR fe ← fileList, fe.link UNTIL fe = NIL DO
      BEGIN
        IF fe.stamp.time = NullTime THEN GO TO loop
        ELSE FileName[fe];
        PutString[" includes"];
        IF fe.includes = NIL THEN PutString[" nothing"]
        ELSE FOR i ← fe.includes, i.link UNTIL i = NIL DO
          badfile ← i.stamp # i.includedFile.stamp AND i.includedFile.stamp # NullStamp AND i.stamp # Nu1
**1Stamp;
          PutCR[];
          PutChar[SP];

```

```

PutChar[IF badfile THEN '* ELSE SP];
FileName[i.includedFile];
IF badfile THEN
  BEGIN
    fe.bad ← TRUE;
    PutString[" included version was "];
    PutStamp[i.stamp];
  END
ELSE IF i.stamp = NullStamp THEN
  PutString[" ** never referenced"];
ENDLOOP;
PutCR[];PutCR[];
EXITS loop => NULL;
END;
ENDLOOP;
PutChar[FF];
printDate ← FALSE;
FOR fe ← fileList, fe.link UNTIL fe = NIL DO
  BEGIN
    FileName[fe];
    PutString[" is included by"];
    IF fe.includedBy = NIL THEN PutString[" nothing"]
    ELSE FOR i ← fe.includedBy, i.link UNTIL i = NIL DO
      PutCR[];
      PutString[" "];
      FileName[i.includedFile];
    ENDLOOP;
    PutCR[];PutCR[];
  END;
END;
ENDLOOP;
END;

Compile: PROCEDURE [fe: FEPtr] =
  BEGIN
    i: POINTER TO IncludeItem;
    IF fe.mark THEN RETURN;
    IF fe.busy THEN
      BEGIN
        PutString["
list of included modules from "];
        PutString[fe.name];
        PutString[" forms a circle
"];
        RETURN
      END;
    fe.busy ← TRUE;
    FOR i ← fe.includes, i.link UNTIL i = NIL DO
      Compile[i.includedFile];
    ENDLOOP;
    PutChar[SP];
    PutString[fe.name];
    fe.mark ← TRUE;
    fe.busy ← FALSE;
  END;

OutputCompileOrder: PROCEDURE =
  BEGIN
    fe: FEPtr;
    PutString["Compilation Order:
"];
    FOR fe ← fileList, fe.link UNTIL fe = NIL DO
      Compile[fe];
    ENDLOOP;
    PutCR[]; PutCR[];
  END;

Init: PROCEDURE =
  BEGIN OPEN SystemDefs;
    fe: FEPtr;
    i: POINTER TO IncludeItem;
    UNTIL fileList = NIL DO
      UNTIL fileList.includes = NIL DO
        i ← fileList.includes.link;
        FreeHeapNode[fileList.includes];
        fileList.includes ← i;
      ENDLOOP;
    END;

```

```

UNTIL fileList.includedBy = NIL DO
  i ← fileList.includedBy.link;
  FreeHeapNode[fileList.includedBy];
  fileList.includedBy ← i;
ENDLOOP;
fe ← fileList.link;
FreeHeapString[fileList.name];
FreeHeapNode[fileList];
fileList ← fe;
ENDLOOP;
RETURN
END;

GetToken: PROCEDURE [name: STRING, in: StreamDefs.StreamHandle] =
BEGIN
  c: CHARACTER;
  name.length ← 0;
  UNTIL in.endof[in] DO
    c ← in.get[in];
    SELECT c FROM
      IODefs.SP, IODefs.CR => IF name.length # 0 THEN RETURN;
    ENDCASE => StringDefs.AppendChar[name, c];
  ENDLOOP;
RETURN
END;

DoWork: PROCEDURE =
BEGIN
  cfa: POINTER TO AltoFileDefs.CFA;
  in: StreamDefs.StreamHandle;
  root: STRING ← [40];
  name: STRING ← [40];
  cfa ← MiscDefs.CommandLineCFA[];
  in ← StreamDefs.CreateByteStream[
    SegmentDefs.InsertFile[@cfa.fp, StreamDefs.Read], StreamDefs.Read];
  StreamDefs.JumpToFA[in, @cfa.fa];
  GetToken[root, in];
  IF root.length = 0 THEN StringDefs.AppendString[root, "Includes"];
  Init[];
  IODefs.WriteChar[IODefs.CR];
  GetToken[name, in];
  UNTIL name.length = 0 DO
    AddName[name];
    GetToken[name, in];
  ENDLOOP;
  DirectoryDefs.EnumerateDirectory[IsBCD];
  OpenOutput[root, ".list"];
  OutputCompileOrder[];
  OutputStats[];
  CloseOutput[];
END;

MyVersion: PROCEDURE RETURNS [version: BcdDefs.VersionStamp] =
BEGIN OPEN SegmentDefs;
  self: ControlDefs.GlobalFrameHandle = REGISTER[ControlDefs.Greg];
  seg: FileSegmentHandle ← NewFileSegment[self.codesegment.file, 1, 1, Read];
  bcd: POINTER TO BcdDefs.BCD;
  SwapIn[seg];
  bcd ← FileSegmentAddress[seg];
  version ← bcd.version;
  Unlock[seg];
  DeleteFileSegment[seg];
RETURN
END;

LoadIncludes: PROCEDURE =
BEGIN OPEN TimeDefs;
  herald: STRING ← [50];
  StringDefs.AppendString[herald, "Alto/Mesa Include Checker "L];
  AppendDayTime[herald, UnpackDT[MyVersion[.time]]];
  herald.length ← herald.length - 3;
  IODefs.WriteLine[herald];
  herald.length ← 0;
  AppendDayTime[herald, UnpackDT[DefaultTime]];
  herald.length ← herald.length - 3;
  IODefs.WriteLine[herald];

```

```
    END;  
-- MAIN BODY CODE  
LoadIncludes[];  
DoWork[];  
ImageDefs.StopMesa[];  
END.
```