

ssh

```
I-BACKEND , no receiver name specified as parameter
I-BACKEND , no 2nd receiver name specified as parameter
I-BACKEND , Continuum total hardware used [%]: 0.0
I-BACKEND , 100kHz total hardware used [%]: 0.0
I-BACKEND , 1MHz total hardware used [%]: 0.0
I-BACKEND , 4MHz total hardware used [%]: 100.0
I-BACKEND , USB total hardware used [%]: 0.0
I-BACKEND , WILMA total hardware requested [%]: 100.0
I-BACKEND , VESPA total hardware used [%]: 33.3
I-BACKEND , 4MHz 1 4.000 4024.0 248.0 E090 horiz U0 none 100.0 none
I-BACKEND , 4MHz 2 4.000 4024.0 -248.0 E090 verti UI none 100.0 none
I-BACKEND , WILMA 1 2.000 3720.0 265.0 E090 horiz U0 none 100.0 none
I-BACKEND , WILMA 2 2.000 3720.0 -265.0 E090 verti UI none 100.0 none
I-BACKEND , WILMA 3 2.000 3720.0 265.0 E230 horiz LI none 100.0 none
I-BACKEND , WILMA 4 2.000 3720.0 265.0 E230 verti LI none 100.0 none
I-BACKEND , VESPA 1 0.040 40.0 0.0 E090 horiz U0 none 90.0 C0-1-0
I-BACKEND , VESPA 2 0.040 40.0 0.0 E090 verti UI none 90.0 myLine2
I-BACKEND , VESPA 3 0.040 40.0 0.0 E230 horiz LI none 90.0
I-BACKEND , VESPA 4 0.040 40.0 0.0 E230 verti LI none 90.0 LILO
```

PAKO> show

```
I-SHOW , paKo Revision v 1.1.1 2009-04-14
I-SHOW , Level. For standard output: 0. For file: 0
I-SHOW , Queue. doSubmit: F
I-SHOW , Project "111-22"
I-SHOW , PI "Dr. Jane D. Doe"
I-SHOW , Observer "John Doe"
I-SHOW , Operator "Pako"
I-SHOW , Topology "LOW"
I-SHOW , Pointing. azimuthCorrection: 0.0000000E+00
I-SHOW , Pointing. elevationCorrection: 0.0000000E+00
I-SHOW , Focus. focusCorrection: 0.0000000E+00
```

PAKO>