

PostgreSQL Tcl Interface Documentation

The PostgreSQL Global Development Group

The Tcl Interface Group

PostgreSQL Tcl Interface Documentation

by The PostgreSQL Global Development Group, The Tcl Interface Group

Table of Contents

1. pgsql - Tcl Binding Library	1
1.1. Overview	1
1.2. Loading pgsql into an Application	2
1.3. pgsql Command Reference	1
pg_connect.....	1
pg_dbinfo.....	1
pg_disconnect.....	1
pg_conndefaults.....	1
pg_exec.....	1
pg_exec_prepared.....	1
pg_result.....	1
pg_select.....	1
pg_execute.....	1
pg_listen.....	1
pg_on_connection_loss.....	1
pg_sendquery.....	1
pg_sendquery_prepared.....	1
pg_getresult.....	1
pg_isbusy.....	1
pg_blocking.....	1
pg_cancelrequest.....	1
pg_quote.....	1
pg_escape_string.....	1
pg_escape_bytea.....	1
pg_unescape_bytea.....	1
pg_lo_creat.....	1
pg_lo_open.....	1
pg_lo_close.....	1
pg_lo_read.....	1
pg_lo_write.....	1
pg_lo_lseek.....	1
pg_lo_tell.....	1
pg_lo_unlink.....	1
pg_lo_import.....	1
pg_lo_export.....	1
1.4. Tcl Namespace Support	2
1.5. Connection/result handles as commands	2
1.6. Example Program.....	2

List of Tables

1-1. pgctl Commands.....	1
--------------------------	---

List of Examples

1-1. pgctl Example Program.....	2
---------------------------------	---

Chapter 1. pgctl - Tcl Binding Library

pgctl is a Tcl package for client programs to interface with PostgreSQL servers. It makes most of the functionality of libpq available to Tcl scripts.

1.1. Overview

Table 1-1 gives an overview over the commands available in pgctl. These commands are described further on subsequent pages.

Table 1-1. pgctl Commands

Command	Namespace Command	Description
pg_connect	pg::connect	open a connection to the server
pg_dbinfo	pg::dbinfo	returns the current connection/result handles
pg_disconnect	pg::disconnect	close a connection to the server
pg_conndefaults	pg::conndefaults	get connection options and their defaults
pg_exec	pg::sqlexec	send a command to the server
pg_exec_prepared	pg::exec_prepared	send a request to execute a prepared statement, with parameters
pg_result	pg::result	get information about a command result
pg_select	pg::select	loop over the result of a query
pg_execute	pg::execute	send a query and optionally loop over the results
pg_quote	pg::quote	escape a string for inclusion into SQL statements
pg_escape_string	pg::escape_string	escape a binary string for inclusion into SQL statements
pg_escape_bytea	pg::escape_bytea	escape a binary string for inclusion into SQL statements
pg_unescape_bytea	pg::unescape_bytea	unescape a binary string from the backend
pg_listen	pg::listen	set or change a callback for asynchronous notification messages
pg_on_connection_loss	pg::on_connection_loss	set or change a callback for unexpected connection loss

Command	Namespace Command	Description
<code>pg_sendquery</code>	<code>pg::sendquery</code>	issue <code>pg_exec</code> -style command asynchronously
<code>pg_sendquery_prepared</code>	<code>pg::sendquery_prepared</code>	send an asynchronous request to execute a prepared statement, with parameters
<code>pg_getresult</code>	<code>pg::getresult</code>	check on results from asynchronously issued commands
<code>pg_isbusy</code>	<code>pg::isbusy</code>	check to see if the connection is busy processing a query
<code>pg_blocking</code>	<code>pg::blocking</code>	set a database connection to be either blocking or nonblocking
<code>pg_cancelrequest</code>	<code>pg::cancelrequest</code>	request PostgreSQL abandon processing of the current command
<code>pg_lo_creat</code>	<code>pg::lo_creat</code>	create a large object
<code>pg_lo_open</code>	<code>pg::lo_open</code>	open a large object
<code>pg_lo_close</code>	<code>pg::lo_close</code>	close a large object
<code>pg_lo_read</code>	<code>pg::lo_read</code>	read from a large object
<code>pg_lo_write</code>	<code>pg::lo_write</code>	write to a large object
<code>pg_lo_lseek</code>	<code>pg::lo_lseek</code>	seek to a position in a large object
<code>pg_lo_tell</code>	<code>pg::lo_tell</code>	return the current seek position of a large object
<code>pg_lo_unlink</code>	<code>pg::lo_unlink</code>	delete a large object
<code>pg_lo_import</code>	<code>pg::lo_import</code>	import a large object from a file
<code>pg_lo_export</code>	<code>pg::lo_export</code>	export a large object to a file

The `pg_lo_*` commands are interfaces to the large object features of PostgreSQL. The functions are designed to mimic the analogous file system functions in the standard Unix file system interface. The `pg_lo_*` commands should be used within a `BEGIN/COMMIT` transaction block because the descriptor returned by `pg_lo_open` is only valid for the current transaction. `pg_lo_import` and `pg_lo_export` *must* be used in a `BEGIN/COMMIT` transaction block.

1.2. Loading pgtcl into an Application

Before using `pgtcl` commands, you must load the `libpgtcl` library into your Tcl application. This is normally done with the `package require` command. Here is an example:

```
package require Pgtcl 1.5
```

`package require` loads the `libpgtcl` shared library, and loads any additional Tcl code that is part of the `Pgtcl` package. Note that you can manually generate the `pkgIndex.tcl` file, or use `make`

`pkgIndex.tcl` or make `pkgIndex.tcl-hand` to have make generate it.

The old way to load the shared library is by using the Tcl `load` command. Here is an example:

```
load libpgtcl[info sharedlibextension]
```

Although this way of loading the shared library is deprecated, we continue to document it for the time being, because it may help in debugging if, for some reason, `package require` is failing. The use of `info sharedlibextension` is recommended in preference to hard-wiring `.so` or `.sl` or `.dll` into the program.

The `load` command will fail unless the system's dynamic loader knows where to look for the `libpgtcl` shared library file. You may need to work with `ldconfig`, or set the environment variable `LD_LIBRARY_PATH`, or use some equivalent facility for your platform to make it work. Refer to the PostgreSQL installation instructions for more information.

`libpgtcl` in turn depends on the interface library `libpq`, so the dynamic loader must also be able to find the `libpq` shared library. In practice this is seldom an issue, since both of these shared libraries are normally stored in the same directory, but it can be a stumbling block in some configurations.

If you use a custom executable for your application, you might choose to statically bind `libpgtcl` into the executable and thereby avoid the `load` command and the potential problems of dynamic linking. See the source code for `pgtclsh` for an example.

1.3. pgtcl Command Reference

pg_connect

Name

`pg_connect` — open a connection to the server

Synopsis

```
pg_connect -conninfo connectOptions ?-connhandle connectionHandleName?  
pg_connect dbName ?-host hostName? ?-port portNumber? ?-tty tty? ?-options serverOption?  
pg_connect -connlist connectNameValueList ?-connhandle connectionHandleName?
```

Description

`pg_connect` opens a connection to the PostgreSQL server.

Three syntaxes are available. In the older one, each possible option has a separate option switch in the `pg_connect` command. In the newer form, a single option string is supplied that can contain multiple

option values. The third form takes the parameters as a name value Tcl list. `pg_conndefaults` can be used to retrieve information about the available options in the newer syntax.

Arguments

New style

connectOptions

`pg_connect` opens a new database connection using the parameters taken from the `connectOptions` string. Unlike the old-style usage of `pg_connect`, with the new-style usage the parameter set can be extended without requiring changes to either `libpgtcl` or the underlying `libpq` library, so use of the new style (or its nonexistent nonblocking analogues `pg_connect_start` and `pg_connect_poll`) is preferred for new application programming.

The passed string can be empty to use all default parameters, or it can contain one or more parameter settings separated by whitespace. Each parameter setting is in the form `keyword = value`. (To write an empty value or a value containing spaces, surround it with single quotes, e.g., `keyword = 'a value'`. Single quotes and backslashes within the value must be escaped with a backslash, i.e., `\'` and `\\`.) Spaces around the equal sign are optional.

The currently recognized parameter key words are:

`host`

Name of host to connect to. If this begins with a slash, it specifies Unix-domain communication rather than TCP/IP communication; the value is the name of the directory in which the socket file is stored. The default is to connect to a Unix-domain socket in `/tmp`.

`hostaddr`

Numeric IP address of host to connect to. This should be in the standard IPv4 address format, e.g., `172.28.40.9`. If your machine supports IPv6, you can also use IPv6 address format, e.g., `fe80::203:93ff:fedb:49bc`. TCP/IP communication is always used when a nonempty string is specified for this parameter.

Using `hostaddr` instead of `host` allows the application to avoid a host name lookup, which may be important in applications with time constraints. However, Kerberos authentication requires the host name. The following therefore applies: If `host` is specified without `hostaddr`, a host name lookup occurs. If `hostaddr` is specified without `host`, the value for `hostaddr` gives the remote address. When Kerberos is used, a reverse name query occurs to obtain the host name for Kerberos. If both `host` and `hostaddr` are specified, the value for `hostaddr` gives the remote address; the value for `host` is ignored, unless Kerberos is used, in which case that value is used for Kerberos authentication. (Note that authentication is likely to fail if `libpq` is passed a host name that is not the name of the machine at `hostaddr`.) Also, `host` rather than `hostaddr` is used to identify the connection in `$HOME/.pgpass`.

Without either a host name or host address, `Pgtcl` will connect using a local Unix domain socket.

`port`

Port number to connect to at the server host, or socket file name extension for Unix-domain connections.

dbname

The database name. Defaults to be the same as the user name.

user

PostgreSQL user name to connect as.

password

Password to be used if the server demands password authentication.

connect_timeout

Maximum wait for connection, in seconds (write as a decimal integer string). Zero or not specified means wait indefinitely. It is not recommended to use a timeout of less than 2 seconds.

options

Command-line options to be sent to the server.

tty

Ignored (formerly, this specified where to send server debug output).

sslmode

This option determines whether or with what priority an SSL connection will be negotiated with the server. There are four modes: `disable` will attempt only an unencrypted SSL connection; `allow` will negotiate, trying first a non-SSL connection, then if that fails, trying an SSL connection; `prefer` (the default) will negotiate, trying first an SSL connection, then if that fails, trying a regular non-SSL connection; `require` will try only an SSL connection.

If PostgreSQL is compiled without SSL support, using option `require` will cause an error, and options `allow` and `prefer` will be tolerated but libpq will be unable to negotiate an SSL connection.

requiressl

This option is deprecated in favor of the `sslmode` setting.

If set to 1, an SSL connection to the server is required (this is equivalent to `sslmode require`). libpq will then refuse to connect if the server does not accept an SSL connection. If set to 0 (default), libpq will negotiate the connection type with the server (equivalent to `sslmode prefer`). This option is only available if PostgreSQL is compiled with SSL support.

service

Service name to use for additional parameters. It specifies a service name in `pg_service.conf` that holds additional connection parameters. This allows applications to specify only a service name so connection parameters can be centrally maintained. See `PREFIX/share/pg_service.conf.sample` for information on how to set up the file.

-connhandle *connectionHandleName*

Name to use for the connection handle, instead of pgtcl generating the name automatically. Without the option, the name is auto-generated, prefixed with `pgsql`, and with a numeric id at the end. This gives the programmer control over the name of the connection handle.

If any parameter is unspecified, then the corresponding environment variable (see `libpq` documentation in the PostgreSQL manual) is checked. If the environment variable is not set either, then built-in defaults are used.

Old style

dbName

The name of the database to connect to.

`-host hostName`

The host name of the database server to connect to.

`-port portNumber`

The TCP port number of the database server to connect to.

`-tty tty`

A file or TTY for optional debug output from the server.

`-options serverOptions`

Additional configuration options to pass to the server.

`-connhandle connectionHandleName`

Name to use for the connection handle, instead of `pgctl` generating the name automatically. Without the option, the name is auto-generated, prefixed with `pgsql`, and with a numeric id at the end. This gives the programmer control over the name of the connection handle.

Third style (most recent one added)

`-connlist connectNameValueList`

`pg_connect` opens a new database connection using the parameters taken from the `connectNameValueList` list. The parameters are exactly the same for the New Style, but they are stored as a Tcl list, instead of a string. The list is a name value pair, for example: `[list host localhost port 5400 dbname template1]`.

```
array set conninfo {
    host    192.168.123.180
    port    5801
    dbname  template1
    user    postgres
}
set conn [pg::connect -connlist [array get ::conninfo]]
```

Return Value

If successful, a handle for a database connection is returned. Handles start with the prefix `pgsql`.

pg_dbinfo

Name

`pg_dbinfo` — returns a list of current open connection/result handles

Synopsis

```
pg_dbinfo connections|results ?conn?
```

Description

`pg_dbinfo` returns a list of connection\result handles that are currently open. The first argument is either `connections` or `results`. If the first argument is `results`, then a second argument needs to be present, specifying the connection.

Arguments

connections/results

Either specify `connections` if you want the connection handles, or `results` if you want the result handles.

conn

The handle of the connection, if `results` is specified for the first argument.

Return Value

A Tcl list of connection handle names

pg_disconnect

Name

`pg_disconnect` — close a connection to the server

Synopsis

```
pg_disconnect conn
```

Description

`pg_disconnect` closes a connection to the PostgreSQL server.

Arguments

conn

The handle of the connection to be closed.

Return Value

None

pg_conndefaults

Name

`pg_conndefaults` — get connection options and their defaults

Synopsis

```
pg_conndefaults
```

Description

`pg_conndefaults` returns information about the connection options available in `pg_connect -conninfo` and the current default value for each option.

Arguments

None

Return Value

The result is a list describing the possible connection options and their current default values. Each entry in the list is a sublist of the format:

```
{optname label dispchar dispsize value}
```

where the *optname* is usable as an option in `pg_connect -conninfo`.

pg_exec

Name

`pg_exec` — send a command to the server

Synopsis

```
pg_exec conn commandString ?args?
```

Description

`pg_exec` submits a command to the PostgreSQL server and returns a result. Command result handles start with the connection handle and add a period and a result number.

Note that lack of a Tcl error is not proof that the command succeeded! An error message returned by the server will be processed as a command result with failure status, not by generating a Tcl error in `pg_exec`.

Arguments

conn

The handle of the connection on which to execute the command.

commandString

The SQL command to execute.

args

For PostgreSQL versions greater than 7.4, *args* consists of zero or more optional values that can be inserted, unquoted, into the SQL statement using $\$$ -style substitution.

Return Value

A result handle. A Tcl error will be returned if `pgtcl` was unable to obtain a server response. Otherwise, a command result object is created and a handle for it is returned. This handle can be passed to `pg_result` to obtain the results of the command.

Example

```
pg_exec $conn {select * from table1 where id = $1 and user = $2} $id $user
```

pg_exec_prepared

Name

`pg_exec_prepared` — send a request to execute a prepared SQL statement to the server

Synopsis

```
pg_exec_prepared conn statementName ?args?
```

Description

`pg_exec_prepared` submits a command to the PostgreSQL server and returns a result.

`pg_exec_prepared` functions identically to `pg_exec`, except that it operates using statements prepared by the `PREPARE SQL` command.

Note that prepared statements are only support under PostgreSQL 7.4 and later.

Arguments

conn

The handle of the connection on which to execute the command.

statementName

The name of the prepared statement to execute.

args

args consists of zero or more optional values that can be inserted, unquoted, into the SQL statement using `$`-style substitution.

Return Value

A result handle. See `pg_exec` for details.

Example

```
pg_exec $conn {prepare insert_people
    (varchar, varchar, varchar, varchar, varchar, varchar)
    as insert into people values ($1, $2, $3, $4, $5, $6);}
```

pg_exec_prepared

pg_exec_prepared \$conn insert_people \$email \$name \$address \$city \$state \$zip

pg_result

Name

`pg_result` — get information about a command result

Synopsis

```
pg_result resultHandle resultOption
```

Description

`pg_result` returns information about a command result created by a prior `pg_exec`.

You can keep a command result around for as long as you need it, but when you are done with it, be sure to free it by executing `pg_result -clear`. Otherwise, you have a memory leak, and `pgctl` will eventually start complaining that you have created too many command result objects.

Arguments

resultHandle

The handle of the command result.

resultOption

One of the following options, specifying which piece of result information to return:

`-status`

The status of the result.

`-error ?diagCode?`

The error message, if the status indicates an error, otherwise an empty string.

diagCode, if specified, requests data for a specific diagnostic code:

severity

The severity; the field contents are `ERROR`, `FATAL`, or `PANIC`, in an error message, or `WARNING`, `NOTICE`, `DEBUG`, `INFO`, or `LOG`, in a notice message, or a localized translation of one of these.

sqlstate

The `SQLSTATE` code for the error. (See PostgreSQL manual Appendix A).

primary

The primary human-readable error message (typically one line).

`detail`

An optional secondary error message carrying more detail about the problem, which may run to multiple lines.

`hint`

An optional suggestion about what to do about the problem. This is intended to differ from detail in that it offers advice (potentially inappropriate) rather than hard facts.

The result may run to multiple lines.

`position`

A string containing a decimal integer indicating an error cursor position as an index into the original statement string.

The first character has index 1, and positions are measured in characters not bytes.

`context`

An indication of the context in which the error occurred. Presently this includes a call stack traceback of active PL functions. The trace is one entry per line, most recent first.

`file`

The filename of the source code location where the error was reported.

`line`

The line number of the source code location where the error was reported.

`function`

The name of the source code function reporting the error.

`-conn`

The connection that produced the result.

`-oid`

If the command was an `INSERT`, the OID of the inserted row, otherwise 0.

`-numTuples`

The number of rows (tuples) returned by the query.

`-cmdTuples`

The number of rows (tuples) affected by the command. (This is similar to `-numTuples` but relevant to `INSERT` and `UPDATE` commands.)

`-numAttrs`

The number of columns (attributes) in each row.

`-assign arrayName`

Assign the results to an array, using subscripts of the form (`rowNumber`, `columnName`).

`-assignbyidx arrayName ?appendstr?`

Assign the results to an array using the values of the first column and the names of the remaining column as keys. If *appendstr* is given then it is appended to each key. In short, all but the first column of each row are stored into the array, using subscripts of the form `(firstColumnValue, columnNameAppendStr)`.

`-getTuple rowNumber`

Returns the columns of the indicated row in a list. Row numbers start at zero.

`-tupleArray rowNumber arrayName`

Stores the columns of the row in array *arrayName*, indexed by column names. Row numbers start at zero.

`-attributes`

Returns a list of the names of the columns in the result.

`-lAttributes`

Returns a list of sublists, `{name typeId typeSize}` for each column.

`-list`

Returns one list containing all the data returned by the query.

`-lList`

Returns a list of lists, where each embedded list represents a tuple in the result.

`-dict`

Returns a dict object with the results. This needs to have dictionary support built into Tcl (Tcl 8.5), and is experimental right now, since Tcl 8.5 has not been release yet, and the API could change. In order to enable this, you need to add `-DHAVE_TCL_NEWDICTOBJ` to the Makefile in the `DEFS` variable.

`-clear`

Clear the command result object.

Return Value

The result depends on the selected option, as described above.

pg_select

Name

`pg_select` — loop over the result of a query

Synopsis

```
pg_select conn commandString arrayVar procedure
```

Description

`pg_select` submits a query (`SELECT` statement) to the PostgreSQL server and executes a given chunk of code for each row in the result. The `commandString` must be a `SELECT` statement; anything else returns an error. The `arrayVar` variable is an array name used in the loop. For each row, `arrayVar` is filled in with the row values, using the column names as the array indices. Then the `procedure` is executed.

In addition to the column values, the following special entries are made in the array:

`.headers`

A list of the column names returned by the query.

`.numcols`

The number of columns returned by the query.

`.tupno`

The current row number, starting at zero and incrementing for each iteration of the loop body.

Arguments

`conn`

The handle of the connection on which to execute the query.

`commandString`

The SQL query to execute.

`arrayVar`

An array variable for returned rows.

procedure

The procedure to run for each returned row.

Return Value

None

Examples

This examples assumes that the table `table1` has columns `control` and `name` (and perhaps others):

```
pg_select $pgconn "SELECT * FROM table1;" array {  
    puts [format "%5d %s" $array(control) $array(name)]  
}
```

pg_execute

Name

`pg_execute` — send a query and optionally loop over the results

Synopsis

```
pg_execute ?-array arrayVar? ?-oid oidVar? conn commandString ?procedure?
```

Description

`pg_execute` submits a command to the PostgreSQL server.

If the command is not a `SELECT` statement, the number of rows affected by the command is returned. If the command is an `INSERT` statement and a single row is inserted, the OID of the inserted row is stored in the variable `oidVar` if the optional `-oid` argument is supplied.

If the command is a `SELECT` statement, then, for each row in the result, the row values are stored in the `arrayVar` variable, if supplied, using the column names as the array indices, else in variables named by the column names, and then the optional `procedure` is executed if supplied. (Omitting the `procedure` probably makes sense only if the query will return a single row.) The number of rows selected is returned.

The `procedure` can use the Tcl commands `break`, `continue`, and `return` with the expected behavior. Note that if the `procedure` executes `return`, then `pg_execute` does not return the number of affected rows.

`pg_execute` is a newer function which provides a superset of the features of `pg_select` and can replace `pg_exec` in many cases where access to the result handle is not needed.

For server-handled errors, `pg_execute` will throw a Tcl error and return a two-element list. The first element is an error code, such as `PGRES_FATAL_ERROR`, and the second element is the server error text. For more serious errors, such as failure to communicate with the server, `pg_execute` will throw a Tcl error and return just the error message text.

Arguments

`-array arrayVar`

Specifies the name of an array variable where result rows are stored, indexed by the column names. This is ignored if `commandString` is not a `SELECT` statement.

`-oid oidVar`

Specifies the name of a variable into which the OID from an `INSERT` statement will be stored.

`conn`

The handle of the connection on which to execute the command.

commandString

The SQL command to execute.

procedure

Optional procedure to execute for each result row of a `SELECT` statement.

Return Value

The number of rows affected or returned by the command.

Examples

In the following examples, error checking with `catch` has been omitted for clarity.

Insert a row and save the OID in `result_oid`:

```
pg_execute -oid result_oid $pgconn "INSERT INTO mytable VALUES (1);"
```

Print the columns `item` and `value` from each row:

```
pg_execute -array d $pgconn "SELECT item, value FROM mytable;" {
    puts "Item=${d(item)} Value=${d(value)}"
}
```

Find the maximum and minimum values and store them in `$s(max)` and `$s(min)`:

```
pg_execute -array s $pgconn "SELECT max(value) AS max, min(value) AS min FROM mytable;"
```

Find the maximum and minimum values and store them in `$max` and `$min`:

```
pg_execute $pgconn "SELECT max(value) AS max, min(value) AS min FROM mytable;"
```

pg_listen

Name

`pg_listen` — set or change a callback for asynchronous notification messages

Synopsis

```
pg_listen conn notifyName ?callbackCommand?
```

Description

`pg_listen` creates, changes, or cancels a request to listen for asynchronous notification messages from the PostgreSQL server. With a *callbackCommand* parameter, the request is established, or the command string of an already existing request is replaced. With no *callbackCommand* parameter, a prior request is canceled.

After a `pg_listen` request is established, the specified command string is executed whenever a notification message bearing the given name arrives from the server. This occurs when any PostgreSQL client application issues a `NOTIFY` command referencing that name. The command string is executed from the Tcl idle loop. That is the normal idle state of an application written with Tk. In non-Tk Tcl shells, you can execute `update` or `vwait` to cause the idle loop to be entered.

You should not invoke the SQL statements `LISTEN` or `UNLISTEN` directly when using `pg_listen`. `pgtcl` takes care of issuing those statements for you. But if you want to send a notification message yourself, invoke the SQL `NOTIFY` statement using `pg_exec`.

Arguments

conn

The handle of the connection on which to listen for notifications.

notifyName

The name of the notification condition to start or stop listening to.

callbackCommand

If present, provides the command string to execute when a matching notification arrives.

Return Value

None

pg_on_connection_loss

Name

`pg_on_connection_loss` — set or change a callback for unexpected connection loss

Synopsis

```
pg_on_connection_loss conn ?callbackCommand?
```

Description

`pg_on_connection_loss` creates, changes, or cancels a request to execute a callback command if an unexpected loss of connection to the database occurs. With a *callbackCommand* parameter, the request is established, or the command string of an already existing request is replaced. With no *callbackCommand* parameter, a prior request is canceled.

The callback command string is executed from the Tcl idle loop. That is the normal idle state of an application written with Tk. In non-Tk Tcl shells, you can execute `update` or `vwait` to cause the idle loop to be entered.

Arguments

conn

The handle to watch for connection losses.

callbackCommand

If present, provides the command string to execute when connection loss is detected.

Return Value

None

pg_sendquery

Name

`pg_sendquery` — send a query string to the backend connection without waiting for a result

Synopsis

```
pg_sendquery conn commandString
```

Description

`pg_sendquery` submits a command to the PostgreSQL server. This function works like `pg_exec`, except that it does not return a result. Rather, the command is issued to the backend asynchronously.

The result is either an error message or nothing. An empty return indicates that the command was dispatched to the backend.

Arguments

conn

The handle of the connection on which to execute the command.

commandString

The SQL command to execute.

Return Value

A Tcl error will be returned if `pgtcl` was unable to issue the command. Otherwise, an empty string will be returned. It is up to the developer to use `pg_getresult` to obtain results from commands issued with `pg_sendquery`.

pg_sendquery_prepared

Name

`pg_sendquery_prepared` — send a request to execute a prepared statement to the backend connection, without waiting for a result

Synopsis

```
pg_sendquery_prepared conn statementName ?args?
```

Description

`pg_sendquery_prepared` submits a command to the PostgreSQL server. This function works like `pg_exec`, except that it does not return a result. Rather, the command is issued to the backend asynchronously.

The result is either an error message or nothing. An empty return indicates that the command was dispatched to the backend.

Arguments

conn

The handle of the connection on which to execute the command.

statementName

The name of the prepared SQL statement to execute asynchronously.

args

args consists of zero or more optional values that can be inserted, unquoted, into the SQL statement using $\$$ -style substitution.

Return Value

A Tcl error will be returned if `pgtcl` was unable to issue the command. Otherwise, an empty string will be return. It is up to the developer to use `pg_getresult` to obtain results from commands issued with `pg_sendquery`.

pg_getresult

Name

`pg_getresult` — process asynchronous results

Synopsis

```
pg_getresult conn
```

Description

`pg_getresult` checks to see if any commands issued by `pg_sendquery` have completed.

This will return the same sort of result handle that `pg_exec` returns.

If there is no query currently being processed or all of the results have been obtained, `pg_getresult` returns nothing.

Arguments

conn

The handle of a connection to the database to which asynchronous requests are being issued.

Return Value

If a query result is available, a command result object is returned. This handle can be passed to `pg_result` to obtain the results of the command.

If there is no query currently being processed or all of the results have been obtained, `pg_getresult` returns nothing.

pg_isbusy

Name

`pg_isbusy` — see if a query is busy

Synopsis

```
pg_isbusy conn
```

Description

`pg_isbusy` checks to see if the backend is busy handling a query or not.

Arguments

conn

The handle of a connection to the database in which the large object exists.

Return Value

Returns 1 if the backend is busy, in which case a call to `pg_getresult` would block, otherwise it returns 0.

pg_blocking

Name

`pg_blocking` — see or set whether or not a connection is set to blocking or nonblocking

Synopsis

```
pg_blocking conn ?mode?
```

Description

`pg_blocking` can set the connection to either blocking or nonblocking, and it can see which way the connection is currently set.

Arguments

conn

The handle of a connection to the database in which the large object exists.

mode

If present, sets the mode of the connection to `nonblocking` if 0. Otherwise it sets the connection to `blocking`.

Return Value

Returns nothing if called with the *mode* argument. Otherwise it returns 1 if the connection is set for `blocking`, or 0 if the connection is set for `nonblocking`.

pg_cancelrequest

Name

`pg_cancelrequest` — request that PostgreSQL abandon processing of the current command

Synopsis

```
pg_cancelrequest conn
```

Description

`pg_cancelrequest` requests that the processing of the current command be abandoned.

Arguments

conn

The handle of a connection to the database in which the large object exists.

Return Value

Returns nothing if the command was successfully dispatched or if no query was being processed. Otherwise, returns an error.

pg_quote

Name

`pg_quote` — escapes a string for inclusion into SQL statements

Synopsis

```
pg_quote string
```

Description

`pg_quote` quotes a string and escapes single quotes and backslashes within the string, making it safe for inclusion into SQL statements.

If you're doing something like

```
pg_exec $conn "insert into foo values ('$name');"
```

and `name` contains text including an unescaped single quote, such as `Bob's House`, the insert will fail. Passing value strings through `pg_quote` make sure they can be used as values and stuff in PostgreSQL.

```
pg_exec $conn "insert into foo values ([pg_quote $name]);"
```

...will make sure that any special characters that occur in `name`, such as single quote or backslash, will be properly quoted.

Arguments

string

The string to be escaped.

Return Value

Returns the string, escaped for inclusion into SQL queries. Note that it adds a set of single quotes around the outside of the string as well.

pg_escape_string

Name

`pg_escape_string` — escapes a string for inclusion into SQL statements. This is the same as `pg_quote`. It was added for consistency.

Synopsis

```
pg_escape_string string
```

Description

`pg_escape_string` quotes a string and escapes single quotes and backslashes within the string, making it safe for inclusion into SQL statements.

If you're doing something like

```
pg_exec $conn "insert into foo values ('$name');"
```

and `name` contains text including an unescaped single quote, such as `Bob's House`, the insert will fail. Passing value strings through `pg_escape_string` make sure they can be used as values and stuff in PostgreSQL.

```
pg_exec $conn "insert into foo values ([pg_escape_string $name]);"
```

...will make sure that any special characters that occur in `name`, such as single quote or backslash, will be properly quoted.

Arguments

string

The string to be escaped.

Return Value

Returns the string, escaped for inclusion into SQL queries. Note that it adds a set of single quotes around the outside of the string as well.

pg_escape_bytea

Name

`pg_escape_bytea` — escapes a binary string for inclusion into SQL statements.

Synopsis

```
pg_escape_bytea string
```

Description

`pg_escape_bytea` escapes a binary string, making it safe for inclusion into SQL statements.

```
pg_exec $conn "insert into foo values ([pg_escape_binary $name]);"
```

Arguments

binary_string

The binary string to be escaped.

Return Value

Returns the binary string, escaped for inclusion into SQL queries.

pg_unescape_bytea

Name

`pg_unescape_bytea` — unescapes a binary string.

Synopsis

```
pg_unescape_bytea string
```

Description

`pg_unescape_bytea` unescapes a binary string, when retrieving from the backend.

Arguments

binary_string

The string to be unescaped.

Return Value

Returns the binary string.

pg_lo_creat

Name

`pg_lo_creat` — create a large object

Synopsis

```
pg_lo_creat conn mode
```

Description

`pg_lo_creat` creates a large object.

Arguments

conn

The handle of a connection to the database in which to create the large object.

mode

The access mode for the large object. It can be any or'ing together of `INV_READ` and `INV_WRITE`.

The “or” operator is `|`. For example:

```
[pg_lo_creat $conn "INV_READ|INV_WRITE"]
```

Return Value

The OID of the large object created.

pg_lo_open

Name

`pg_lo_open` — open a large object

Synopsis

```
pg_lo_open conn oid mode
```

Description

`pg_lo_open` opens a large object.

Arguments

conn

The handle of a connection to the database in which the large object exists.

oid

The OID of the large object.

mode

Specifies the access mode for the large object. Mode can be either `r`, `w`, or `rw`.

Return Value

A descriptor for use in later large-object commands.

pg_lo_close

Name

`pg_lo_close` — close a large object

Synopsis

```
pg_lo_close conn descriptor
```

Description

`pg_lo_close` closes a large object.

Arguments

conn

The handle of a connection to the database in which the large object exists.

descriptor

A descriptor for the large object from `pg_lo_open`.

Return Value

None

pg_lo_read

Name

`pg_lo_read` — read from a large object

Synopsis

```
pg_lo_read conn descriptor bufVar len
```

Description

`pg_lo_read` reads at most *len* bytes from a large object into a variable named *bufVar*.

Arguments

conn

The handle of a connection to the database in which the large object exists.

descriptor

A descriptor for the large object from `pg_lo_open`.

bufVar

The name of a buffer variable to contain the large object segment.

len

The maximum number of bytes to read.

Return Value

The number of bytes actually read is returned; this could be less than the number requested if the end of the large object is reached first. In event of an error, the return value is negative.

pg_lo_write

Name

`pg_lo_write` — write to a large object

Synopsis

```
pg_lo_write conn descriptor buf len
```

Description

`pg_lo_write` writes at most *len* bytes from a variable *buf* to a large object.

Arguments

conn

The handle of a connection to the database in which the large object exists.

descriptor

A descriptor for the large object from `pg_lo_open`.

buf

The string to write to the large object (not a variable name, but the value itself).

len

The maximum number of bytes to write. The number written will be the smaller of this value and the length of the string.

Return Value

The number of bytes actually written is returned; this will ordinarily be the same as the number requested. In event of an error, the return value is negative.

pg_lo_lseek

Name

`pg_lo_lseek` — seek to a position of a large object

Synopsis

```
pg_lo_lseek conn descriptor offset whence
```

Description

`pg_lo_lseek` moves the current read/write position to *offset* bytes from the position specified by *whence*.

Arguments

conn

The handle of a connection to the database in which the large object exists.

descriptor

A descriptor for the large object from `pg_lo_open`.

offset

The new seek position in bytes.

whence

Specified from where to calculate the new seek position: `SEEK_CUR` (from current position), `SEEK_END` (from end), or `SEEK_SET` (from start).

Return Value

None

pg_lo_tell

Name

`pg_lo_tell` — return the current seek position of a large object

Synopsis

```
pg_lo_tell conn descriptor
```

Description

`pg_lo_tell` returns the current read/write position in bytes from the beginning of the large object.

Arguments

conn

The handle of a connection to the database in which the large object exists.

descriptor

A descriptor for the large object from `pg_lo_open`.

Return Value

A zero-based offset in bytes suitable for input to `pg_lo_lseek`.

pg_lo_unlink

Name

`pg_lo_unlink` — delete a large object

Synopsis

```
pg_lo_unlink conn oid
```

Description

`pg_lo_unlink` deletes the specified large object.

Arguments

conn

The handle of a connection to the database in which the large object exists.

oid

The OID of the large object.

Return Value

None

pg_lo_import

Name

`pg_lo_import` — import a large object from a file

Synopsis

```
pg_lo_import conn filename
```

Description

`pg_lo_import` reads the specified file and places the contents into a new large object.

Arguments

conn

The handle of a connection to the database in which to create the large object.

filename

Specified the file from which to import the data.

Return Value

The OID of the large object created.

Notes

`pg_lo_import` must be called within a `BEGIN/COMMIT` transaction block.

pg_lo_export

Name

`pg_lo_export` — export a large object to a file

Synopsis

```
pg_lo_export conn oid filename
```

Description

`pg_lo_export` writes the specified large object into a file.

Arguments

conn

The handle of a connection to the database in which the large object exists.

oid

The OID of the large object.

filename

Specifies the file into which the data is to be exported.

Return Value

None

Notes

`pg_lo_export` must be called within a `BEGIN/COMMIT` transaction block.

1.4. Tcl Namespace Support

With version 1.5, there is proper Tcl namespace support built into *pgtcl*. There are commands now that mirror the *pg_* commands, but use the Tcl namespace convention. For example, there are commands now called: *pg::connect*, *pg::result*, etc. However, due to this, there are some incapacibilities. For example, *pg_exec* has a counterpart called *pg::sqlxec*, since doing a namespace import *::pg::** would clobber the builtin Tcl command *exec*. The old command names, *pg_**, are still there for backwards compatibility, but might be phased out eventually.

So, one can use Tcl's namespace mechanisms now with *pgtcl*. For example, you can import that namespace:

```
namespace import ::pg::*

set conn [connect template1 -host $host -port $port]
```

1.5. Connection/result handles as commands

Starting with version 1.5, you can use the connection/result handle as a Tcl command. What this means is that when a handle for a connection or result is generated, a corresponding Tcl command is also generated. For example, you can do the following:

```
set conn [pg::connect template1 -host $host -port $port]
set res [$conn exec "SELECT datname FROM pg_database ORDER BY datname;"]
set datnames [$res -list]
$res -clear
rename $conn {} ;# or $conn disconnect
```

Note that deleting the command (*rename \$conn {}*), has the same effect as *pg::result \$res -clear* (if it is a result handle), and *pg::disconnect* (if it is a connection handle). Also, if that command gets overloaded with a proc definition, then that has the same effect as deleting the command.

1.6. Example Program

Example 1-1 shows a small example of how to use the *pgtcl* commands.

Example 1-1. *pgtcl* Example Program

```
# getDBs :
#  get the names of all the databases at a given host and port number
#  with the defaults being the localhost and port 5432
#  return them in alphabetical order
proc getDBs { {host "localhost"} {port "5432"} } {
    # datnames is the list to be result
    set conn [pg_connect template1 -host $host -port $port]
    set res [pg_exec $conn "SELECT datname FROM pg_database ORDER BY datname;"]
    set ntups [pg_result $res -numTuples]
    for {set i 0} {$i < $ntups} {incr i} {
```

```

lappend datnames [pg_result $res -getTuple $i]
    }
    pg_result $res -clear
    pg_disconnect $conn
    return $datnames
}

## OR an alternative

proc getDBs { {host "localhost"} {port "5432"} } {
    # datnames is the list to be result
    set conn [pg_connect template1 -host $host -port $port]
    set res [pg_exec $conn "SELECT datname FROM pg_database ORDER BY datname;"]

    set datnames [pg_result $res -list]
    pg_result $res -clear
    pg_disconnect $conn
    return $datnames
}

## OR an alternative

proc getDBs { {host "localhost"} {port "5432"} } {
    # datnames is the list to be result
    set conn [pg_connect template1 -host $host -port $port]
    set res [$conn "SELECT datname FROM pg_database ORDER BY datname;"]

    set datnames [$res -dict]
    $res -clear
    rename $conn {}
    return [dict get $datnames]
}

```