


The **LTC<sup>®</sup>1064-3** data sheet has been modified from Rev 0 to Rev A. The changes are shown below and are indicated in **bold** type. For complete specifications, typical performance curves and applications information, please see the **LTC1064-3** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

## ELECTRICAL CHARACTERISTICS

$V_S = \pm 7.5V$ , 75:1,  $f_{CLK} = 2MHz$ ,  $R_L = 10k$ ,  $T_A = 25^\circ C$ , TTL or CMOS clock input level, unless otherwise specified.

PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage Swing and Operating Input Voltage Range	$V_S = \pm 2.37V$	●	$\pm 1.1$			V
	$V_S = \pm 5V$	●	$\pm 3.1$			V
	$V_S = \pm 7.5V$	●	$\pm 5$			V
Power Supply Current	$V_S = \pm 2.37V$ , $f_{CLK} = 1MHz$	●		10	<b>22</b>	mA
	$V_S = \pm 5V$ , $f_{CLK} = 1MHz$	●		12	<b>23</b>	mA
					<b>26</b>	mA
	$V_S = \pm 7.5V$ , $f_{CLK} = 1MHz$	●		16	<b>28</b> <b>32</b>	mA mA

For further information regarding this specification notice contact:

Linear Technology Corporation  
 1630 McCarthy Blvd.  
 Milpitas, California 95035-7417  
 Attn: Product Marketing Manager  
 Phone: (408) 432-1900, Ext. 2456