


Comparators


InfoCard 10

Response Time	MAXIMUM V_{OS}					TTL OUTPUTS	ECL OUTPUTS	OPEN-DRAIN COLLECTOR	QUAD	DUAL	SINGLE	GROUND SENSE	MICRO- POWER	ADDITIONAL COMMENTS
	20mV	10mV	≤ 3 mV	≤ 2 mV	1mV									
100 μ s						LTC [®] 1040				LTC1040		LTC1040	LTC1040	Sampling: Consumes 1.5 μ W at 1 Sample/Sec.
						LTC1041					LTC1041	LTC1041	LTC1041	Bang-Bang Controller: 1.5 μ W at Sample/Sec.
15 μ s						LTC1042					LTC1042	LTC1042	LTC1042	Sampling Window Comp.: 1.5 μ W at 1 Sample/Sec.
12 μ s						LT [®] 1017					LT1017	LT1017	LT1017	60 μ A Max. I_{CC} /Operates to 1.1V
						LTC1443/4/5					LTC1443/4/5	LTC1443/4/5	LTC1443/4/5	Built-in Reference: (1.182V or 1.221V) 8.5 μ A Supply Current
						LTC1441					LTC1441	LTC1441	LTC1441	6 μ A Supply Current
						LTC1440/2					LTC1440/2	LTC1440/2	LTC1440/2	Built-in Reference: (1.182V) 6 μ A Supply Current
4 μ s						LT1018					LT1018	LT1018	LT1018	250 μ A Max. I_{CC} /Operates to 1.1V
250ns						LT1011					LT1011			12-Bit Accurate
14ns						LT1011A								High Speed Two-Channel Line Receiver
						LT1015					LT1015			Ground Sense/Single Supply
12ns						LT1116					LT1116	LT1116		No Min. Input Slew Rate Requirement/Latched Output
						LT1016					LT1016			
6.5ns						LT685					LT685			Latched ECL Outputs

LTC1440 Maintains Microamp Supply Current Over Industrial Temperature Range



LT1016 Doesn't Oscillate with Slowly Changing Input Signals



LTC and LT are registered trademarks of Linear Technology Corporation.

Linear Technology Corporation • 1630 McCarthy Blvd. • Milpitas, CA 95035-7417 • (408) 432-1900 • www.linear-tech.com • Literature Only: 1-800-4-LINEAR

Rev G 0496

Positive Regulators

I _{OUT}	PART NUMBER	DROPOUT VOLTAGE	MICRO-POWER	ADJUST-ABLE	FIXED OUTPUT VOLTAGES AVAILABLE	REMOTE SENSE	SHUTDOWN	DUAL OUTPUT	HIGH VOLTAGE	LOW-BATT DETECTOR	SURFACE MOUNT PACKAGE
125mA	LT1020	0.4V	☑	☑		☑	☑			☑	SOL
	LT1120	0.4V	☑	☑		☑	☑			☑	S8
	LT1120A	0.4V	☑	☑		☑	☑			☑	S8
150mA	LT1121	0.42V	☑	☑			☑			☑	S8, SOT223
300mA	LT1521	0.5V	☑	☑	3, 3.3, 5		☑				S8, SOT223
500mA	LT317AH	3V		☑					(LT317AHVH)		
	LT1086	0.95V	☑	☑							
800mA	LT1129	0.4V				☑	☑				S8, DD, SOT223
	LT1117	1.1V									SOT223, DD
1A	LT1005	2V			5		☑	☑			
1.5A	LT317A	3V		☑					(LT317AHVK)		
	LT1086	1.3V		☑	2.85, 3.3, 3.6, 5, 12						DD
3A	LT323A	2.5V			5						
	LT350A	3V		☑							
	LT1035	2.2V			5V/3A, 5V/75mA		☑	☑			
	LT1036	2.4V			5V/75mA, 12V/3A		☑	☑			
	LT1085	1.3V		☑							DD (-3.3, -3.6 Only)
	LT1587	1.1V		☑	3.3, 3.45, 3.6						DD
	LT1528	0.6V		☑	3.3		☑				DD
	LT1529	0.5V	☑	☑	3.3, 5		☑				DD
4A	LT1585	1.1V			3.38, 3.45, 3.6						DD (Also 3.38, 3.45V)
4.6A	LT1585	1.1V		☑	3.3						DD
5A	LT1585A	1.1V		☑	3.3						DD
	LT338A	3V		☑							
	LT1003	2.5V			5						
	LT1084	1.3V		☑	3.3, 5, 12						
	LT1087	1.3V		☑		☑					
7A	LT1584	1.1V		☑	3.3, 3.38, 3.45, 3.6						
	LT1580	0.45V		☑	2.5	☑	☑				
7.5A	LT1083	1.3V		☑	5, 12						
10A	LT1038	3V		☑							

Negative Regulators


500mA	LT337A	3V		☑					(LT337AHVH)		
800mA	LT1175	0.45V	☑	☑	5		☑				DD, S8
1.5A	LT337A	3V		☑					(LT337AHVK)		
3A	LT1033	3V		☑							
	LT1185	0.8V		☑		☑	☑				

Discrete PNP Pass Element Driver and Regulators


	LT1123	0.45V				☑					SOT223
--	--------	-------	--	--	--	---	--	--	--	--	--------

Not all output voltage variations are available in the indicated surface mount packages. Please consult factory for availability.

LT1120A/LT1121: Lowest Quiescent Current, Best Efficiency



Easy 5V to V_{CC} for New Microprocessors



I _{OUT}	2.5V	3.3V	3.38V*	3.45V	3.6V	4.0V
1.5A	—	LT1086-3.3	—	LT1086	LT1086-3.6	
3A	—	LT1587-3.3	—	LT1587-3.45	LT1587-3.6	
	—	LT1528	LT1528	LT1528	LT1528	LT1528
4A	—	LT1585-3.3	LT1585-3.38	LT1585-3.45	LT1585-3.6	
4.6A	—	LT1585-3.3	LT1585-3.38	LT1585-3.45	LT1585-3.6	
5A	LT1580-2.5	LT1585A-3.3	—	—	—	
	LT1580-2.5	LT1584-3.3	LT1584-3.38	LT1584-3.45	LT1584-3.6	
7A	—	LT1580	LT1580*	LT1580	LT1580	LT1580
7.5A	—	LT1083	—	LT1083	LT1083	
10A	—	2 × LT1087	—	2 × LT1087	2 × LT1087	

*3.3V +5/-0%: Perfect for Pentium® Processors

- SMT Packages up to 4.6A
- Three Terminal Regulators; No Design Required